



# WFM TD-8000IM Metal Halide Lighting Tower with 8.8 kVA Genset

## Product description:

### Key features of the WFM TD-8000IM lighting tower

- Lighting tower hidraulic 9 mt.
- Mast rotation 360°
- 4 1000W metal halide floodlights
- Genset and alternator of leading brands
- Tank 140 lt., operating time 85 hours
- Noise 65 dbA at 7 meters.
- Stabilizer feet and parking brake for a high level of operational safety
- Full load test with test certificate
- User's manual in compliance with safety regulations

Le immagini sono puramente indicative.

### Product features:

Phase: Single phase

Maximum power single phase (KW): 7

Maximum power single phase (KVA): 8.8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 32A

Engine: Perkins 403D-1163

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 1131

Number cylinders: 3

---

Oil capacity (L): 6  
Type of lamps: Metal halide  
Lamps: 4 x 1000 W  
Telescopic pole: Galvanized steel  
Total lumens (Lm): 80000  
Lifting System: Hydraulic lifting system  
Maximum height (m): 9  
Mast rotation: 360°  
Open size (mm): 2450 x 2800 x 9200  
Length closed (mm): 2450  
Width closed (mm): 1300  
Height closed (mm): 2300  
Transportability: Fast Trailer  
Fuel tank capacity (L): 140  
Consumption (L/h): 1.64 at 100% of the load  
Running time (h): 85 at 100% of the load  
Acoustic power: 90 dB(A)  
Acoustic pressure: 65 dB(A) at 7 m  
Dry weight (Kg): 1030