



WFM TD-8000IM Metal Halide Lighting Tower with 8.8 kVA Genset

Product description:

Key features of the WFM TD-8000IM lighting tower

- Lighting tower hidraulic 9 mt.
- Mast rotation 360°
- 4 1000W metal halide floodlights
- Genset and alternator of leading brands
- Tank 140 lt., operating time 85 hours
- Noise 65 dbA at 7 meters.
- Stabilizer feet and parking brake for a high level of operational safety
- Full load test with test certificate
- User's manual in compliance with safety regulations

Le immagini sono puramente indicative.

Product features:

Phase: Single phase

Maximum power single phase (KW): 7

Maximum power single phase (KVA): 8.8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 32A

Engine: Perkins 403D-1163

Starting system: Electric

Engine capacity (cm³): 1131

Number cylinders: 3

Oil capacity (L): 6
Type of lamps: Metal halide
Lamps: 4 x 1000 W
Telescopic pole: Galvanized steel
Total lumens (Lm): 80000
Lifting System: Hydraulic lifting system
Maximum height (m): 9
Mast rotation: 360°
Open size (mm): 2450 x 2800 x 9200
Length closed (mm): 2450
Width closed (mm): 1300
Height closed (mm): 2300
Transportability: Fast Trailer
Fuel tank capacity (L): 140
Consumption (L/h): 1.64 at 100% of the load
Running time (h): 85 at 100% of the load
Acoustic power: 90 dB(A)
Acoustic pressure: 65 dB(A) at 7 m
Dry weight (Kg): 1030