

GENSET MG 8000 BS/HA - SINGLE-PHASE GENERATOR 6.2 KVA AVR



Product price:

3.156,00 € tax excluded

Product description:

GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

GENSET MG 8000 BS/HA Single-phase generating set with Honda GX 390 OHV STAGE V engine powered by gasoline, capable of delivering a maximum power of 7 KVA complete with AVR voltage regulator.

The GENSET MG 8000 BS/HA generator set is compact and easy to use, equipped with a casing that lowers noise emissions and makes it super-silenced.

The GENSET MG 8000 BS/HA is equipped with electric start with 12 V battery and low fuel consumption, in fact it consumes only 3.3 liters/hour at 75% load.

The generator set GENSET MG 8000 BS/HA is part of the silenced series and are characterized by lower consumption and a longer life expectancy than the range powered by gasoline and equipped with soundproof cabin suitable for installation and outdoor use, and increased tank. The GENSET MG 8000 BS/HA generator set at 3000 rpm is suitable for emergency use only. It is not recommended to use it for more than 6 continuous hours and for more than 500 hours per year.

TECHNICAL FEATURES GENSET MG 8000 BS/HA

Phase Type: Single-Phase
Maximum Single-Phase Power: 7 KVA / 5.6 KW
VAC Voltage: 230 / 400 V
Frequency (Hz): 50
Quadro Starter: Manual with self-winding
Motor: Honda GX 390 OHV
Emission Standard: STAGEV

RPM: 3000
Power supply: Gasoline
Fuel tank capacity: 10.5 l
Consumption @ 75 % load: 3.3 l/h
Autonomy @ 75 % load: 3.18 h
Sound pressure: 86 dB(A)
Length: 1059 mm
Width: 670 mm
Height: 740 mm
Net weight: 138 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase
Maximum power single phase (KW): 5.6
Maximum power single phase (KVA): 7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE
Engine: Honda GX390, 4 stroke, OHV
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 390
Number cylinders: 1
Cooling: Air
Alternator: Synchronous
Protection degree: IP23
Motor insulation class: H
Fuel tank capacity (L): 10.5
Consumption (L/h): 3.3
Running time (h): 3.18
Acoustic power: 86 dB(A)
Acoustic pressure: 61 dB(A) at 7 m
Length (mm): 1059
Width (mm): 670
Height (mm): 740

Dry weight (Kg): 138

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda