



GENSET MG 6001 SS-Y - GENERATOR 6 KVA

Product price:

3.755,35 € tax excluded

Product description:

GENSET MG 6001 SS-Y SINGLE PHASE GENERATOR 6KVA

GENSET MG 6001 SS-Y Singlephase generating with Yanmar L100V diesel engine, capable of delivering a maximum power of 6KVA.

The GENSET MG 6001 SS-Y generator is compact and easy to use, equipped with enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 6001 SS-YY is a 6KVA single-phase diesel generator with electric start. This generator is also available in a version with automatic panel and remote control.

Thanks to its compact size and very low weight, the MG 6001 SS-Y is a lightweight generator that is easy to transport. The GENSET MG 6001 SS-Y also has a low fuel consumption: only 1.5 Lt/h at 75% of the load.

The GENSET MG 6001 SS-Y generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The MG 6001 SS-Y generator is ideal for various types of work: from small hobby work to large construction sites.

The generating set GENSET MG 6001 SS-Y includes:

- Automatic engine stop device with warning lights for:
 - Battery charge failure
 - Battery failure - battery charge failure
 - low fuel level
 - low oil pressure
- Built-in 12 V battery



- 1 single-phase socket CEE 230V - 32A
- 1 single-phase socket CEE 230V - 16A
- Protections for power outputs
- Emergency differential switch
- Emergency stop button
- Fuel level indicator
- Hour meter
- Central lifting hook
- Ready for operation in AMF-ATS or Remote Control

Phase Type: SinglePhase

Maximum SinglePhase Power: 6 KVA / 4.8 KW

Continuous SinglePhase Power: 5.4 KVA / 4.3 KW

VAC Voltage: 230 V

Frequency (Hz): 50

Starting Frame: Electric

Motor: Yanmar L100V

Emission Standard: Stage V

RPM: 3000

Power supply: Diesel

Fuel tank capacity: 30 l

Consumption @ 75 % of load: 1.5 l/h

Autonomy @ 75 % of load: 20 h

Sound pressure: 92 dB(A)

Length: 1160 mm

Width: 631 mm

Height: 872 mm

Net weight: 200 Kg

Are you looking for a generator with different technical characteristics? Here you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5.4

Continuous power single phase (KW): 4.32

Maximum power single phase (KVA): 6

Continuous power single phase (KVA): 4.8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE - 1 x 110V 16A CEE - 1 x 110V 32A CEE

Engine: Yanmar L100V, 4 stroke

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 435

Number cylinders: 1

Cooling: Air

Protection degree: IP23

Motor insulation class: H

Fuel tank capacity (L): 30

Consumption (L/h): 1.5

Running time (h): 20

Acoustic power: 92 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 1160

Width (mm): 631

Height (mm): 872

Dry weight (Kg): 200

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: No

Engine manufacturer: Yanmar