



GENSET MG 6/5 S-Y - SINGLE-PHASE/THREE-PHASE GENERATOR 6.3 KVA

Product price:

3.475,10 € tax excluded

Product description:

GENSET MG 6/5 S-Y SINGLE PHASE / THREE PHASE GENERATOR 6,3KVA

GENSET MG 6/5 S-Y SinglePhase / ThreePhase generating set with Yanmar L100V Stage V diesel engine, capable of delivering a maximum power of 6,3KVA with AVR **Optional** voltage regulator.

The GENSET MG 6/5 S-Y generator set is compact and easy to use, equipped with an enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 6/5 S-Y is a 6,3KVA singlephase/threephase diesel generator set with electric start. This generator is also available in the version with AVR voltage regulator, with automatic panel and remote control.

Thanks to its compact size and very low weight, the GENSET MG 6/5 S-Y is a lightweight generator that is easy to transport. The GENSET MG 6/5 S-Y also has a low fuel consumption: only 1.5 Lt/h at 75% load.

The GENSET MG 6/5 S-Y generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The generating set GENSET MG 6/5 S-Y includes:

- Voltmeter
- Hour meter
- Differential magnetothermal switch
- Emergency stop button
- Starting battery



- 1 threephase socket CEE 16A, 400V - 50 Hz
- 1 singlephase socket CEE 16A, 230V - 50 Hz
- Protection for power outlets
- Arrangement for operation in AMF/ATS or remote control
- Central lifting hook

TECHNICAL FEATURES GENSET MG 6/5 S-Y

Phase Type: Singlephase / Threephase

Maximum Singlephase Power: 2.1 KVA / 1.68 KW

Maximum Threephase Power: 6,3KVA / 5.04 KW

VAC Voltage: 230 / 400 V

Frequency (Hz): 50

Starting Frame: Electric

Motor: : Yanmar L100V

Emission Standard: Stage V

RPM: 3000

Power supply: Diesel

Fuel tank capacity: 10.5 l

Consumption @ 75 % load: 1.5 l/h

Autonomy @ 75 % load: 7 h

Acoustic pressure: 97 dB(A)

Length: 815 mm

Width: 560 mm

Height: 730 mm

Net weight: 150 Kg

Are you looking for a generator with different technical characteristics? Here you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 1.68

Maximum power single phase (KVA): 2.1

Maximum power three phase (KW): 5.04

Maximum power three phase (KVA): 6.3

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 2 x monofase Schuko 230 V





Engine: Yanmar L100N, 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 435
Number cylinders: 1
Cooling: Air
Alternator: Synchronous
Protection degree: IP23
Motor insulation class: H
Fuel tank capacity (L): 10.5
Consumption (L/h): 1.5
Running time (h): 7
Acoustic power: 97 dB(A)
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 815
Width (mm): 560
Height (mm): 730
Dry weight (Kg): 150
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: Compound / AVR (optional)
Engine manufacturer: Yanmar

