



GENSET MG 10/6 S-R - SI NGLE-PHASE/THREE-PHASE GENERATOR 10 KVA

Product price:

5.184,62 € tax excluded

Product description:

GENSET MG 10/6 S-R SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

GENSET MG 10/6 S-R Singlephase / threephase generating set with Lombardini 25LD330/2 diesel engine, capable of delivering a maximum power of 10KVA with AVR **Optional** voltage regulator.

The GENSET MG 10/6 S-R generator set is compact and easy to use, equipped with enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 10/6 S-R is a 10 KVA singlephase/threephase diesel generator set with electric start. This generator is also available in the version with AVR voltage regulator, with automatic panel and remote control.

Thanks to its compact size and very low weight, the GENSET MG 10/6 S-R is a lightweight generator that is easy to transport.

The GENSET MG 10/6 S-R also has a low fuel consumption: only 2.2 Lt/h at 75% load.

The GENSET MG 10/6 S-R generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The generating GENSET MG 10/6 S-R includes:

- Voltmeter
- Hour meter
- Differential magnetothermal switch
- Emergency stop button
- Starting battery





- 1 threephase socket CEE 16A, 400V 50 Hz
- 1 singlephase socket CEE 32A, 230V 50 Hz
- 1 singlephase socket CEE 16A, 230V 50 Hz
- Protection for power outputs
- Arrangement for operation in AMF/ATS or remote control
- Voltmetric switch
- Central lifting hook

TECHNICAL FEATURES GENSET MG 10/6 S-R

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Power: 8.3 KVA / 6.64 KW Maximum ThreePhase Power: 10 KVA / 8 KW

VAC Voltage: 230 / 400 V

Frequency (Hz): 50 Starting Frame: Electric

Engine: Lombardini 25LD330/2
Emission Regulations: Non-emitting

RPM: 3000

Power supply: Diesel Fuel tank capacity: 10.5 l

Consumption @ 75 % load: 2.2 l/h Autonomy @ 75 % load: 4.77 h Sound pressure: 97 dB(A)

Length: 1000 mm Width: 560 mm Height: 730 mm Net weight: 190 Kg

Are you looking for a generator with different technical characteristics? Here you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 6.64 Maximum power single phase (KVA): 8.3 Maximum power three phase (KW): 8 Maximum power three phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50





Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A CEE - 1 x 230V 16A CEE - 1 x 230V 32A CEE

Engine: Lombardini 25LD330.2, 4 stroke Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 654

Number cylinders: 2

Cooling: Air

Alternator: Synchronous Protection degree: IP23 Motor insulation class: H Fuel tank capacity (L): 10.5 Consumption (L/h): 2.2 Running time (h): 4.77 Acoustic power: 97 dB(A)

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 1000 Width (mm): 560 Height (mm): 715 Dry weight (Kg): 190

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: Optional Voltage regulator: AVR (optional) Engine manufacturer: Lombardini