

# GENSET MG 10000 S-KL - GENERATOR 10 KVA



**Product price:**

**6.502,00 € tax excluded**

## **Product description:**

GENSET MG 10000 S-KL SINGLE-PHASE POWER GENERATOR 10KVA STAGE V

GENSET MG 10000 S-KL Single-phase genset with Kubota D1105 STAGE V diesel-powered engine, capable of delivering a maximum power of 10KVA complete with AVR voltage regulator for autonomy up to about 24h.

The GENSET MG 10000 S-KL single-phase genset with autonomy of about 24 hours is compact and easy to use, equipped with an enclosure that lowers noise emissions and makes it super-silent.

The GENSET MG 10000 S-KL is a single-phase 10KVA diesel genset with electric start. This generator is also available in a version with AVR voltage regulator, with automatic panel and remote control.

Thanks to its compact dimensions and very low weight, the GENSET MMG 10000 S-KL is a light generator that is easy to transport.

The GENSET MG 10000 S-KL also has a low fuel consumption: only 2 Lt/h at 75% load for an autonomy of up to approx. 24 h.

The GENSET MG 10000 S-KL generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work requiring an autonomy of about 24h: from small hobby work to large construction sites.

The GENSET MG 10000 S-KL generator set includes:

- Automatic engine stop device with warning lights for:
  - battery charge failure
  - high water temperature
  - low fuel level
  - low oil pressure

- 1 single-phase CEE 230V - 32A outlet
- 1 single-phase 230V withdrawal
- 12 V battery
- Power output protections
- Differential switch
- Voltmeter
- Hour meter
- Emergency stop button
- Fork pass

#### TECHNICAL FEATURES GENSET MG 10000 S-KL

Phase Type: Single-Phase

Maximum Single-Phase Power: 10 KVA / 8 KW

Continuous Single-Phase Power: 9 KVA / 7.2 KW

VAC Voltage: 230 V

Frequency (Hz): 50

Starting Frame: Electric

Engine: Kubota D1105

Emissions Standard: STAGE V

RPM: 1500

Power supply: Diesel

Fuel tank capacity: 40 l

Consumption @ 75 % load: 2 l/h

Autonomy @ 75 % load: 20 h

Acoustic pressure: 95 dB(A)

Length: 1357 mm

Width: 707 mm

Height: 942 mm

Net weight: 350 Kg

Are you looking for a generator with different technical characteristics? Here you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

#### Product features:

Phase: Single phase

Maximum power single phase (KW): 8

Continuous power single phase (KW): 7.2

Maximum power single phase (KVA): 10

Continuous power single phase (KVA): 9

---

Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 230V 32A  
Engine: Kubota D1105  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1123  
Number cylinders: 3  
Cooling: Water  
Alternator: Synchronous  
Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 40  
Consumption (L/h): 2  
Running time (h): 20  
Acoustic power: 95 dB(A)  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 1357  
Width (mm): 707  
Height (mm): 942  
Dry weight (Kg): 350  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: Capacitor  
Engine manufacturer: Kubota