



THREE-PHASE GENERATING SET 70 KVA

Product price:

14.309,00 € tax excluded

Product description:

Standard equipment - Logic with digital display for reading the following parameters: three-phase generator voltage, three-phase mains voltage, battery voltage, amperage, frequency, hour meter, oil pressure (optional on request), engine temperature (optional on request), fuel level, failed start; with automatic engine stop device with alarm signal on the display in the event of: failed start, emergency stop, low oil pressure, low fuel level, high water temperature, oil pressure probe failure, alternator over/under voltage, alternator over/under frequency, opening of power draw door

- Ready for ATS or remote control operation
- Ready for refuelling from external auxiliary tank
- 12 V battery
- Three-phase 400V battery
- Emergency stop button
- Automatic voltage regulator (AVR)
- Central lifting hook

- Fork passage

- Liquid collection tank

The image is purely indicative

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 17.6

Maximum power single phase (KVA): 22

Maximum power three phase (KW): 52.8

Continuous power three phase (KW): 48

Maximum power three phase (KVA): 66

Continuous power three phase (KVA): 60

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x trifase CEE 63 A- 1 x trifase CEE 32 A- 1 x monofase CEE 32 A- 1 x monofase CEE 16 A

Engine: Yanmar L70N

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 4500

Number cylinders: 4

Cooling: Water

Alternator: Synchronous

Fuel tank capacity (L): 195

Consumption (L/h): 10.2 at 75% of the load

Running time (h): 19 at 75% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 2400

Width (mm): 950

Height (mm): 1500

Dry weight (Kg): 1280

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco