



# MASE EA 30 GH



Product price:

**922,50 € tax excluded**

## Product description:

MASE EA 30 GH SINGLE PHASE GENERATOR 2.4KW

MASE EA 30 GH is a single phase generator equipped with Honda GX160 gasoline engine, capable of delivering a maximum power of 2.4KW.

The MASE EA 30 GH singlephase generator provides reliable power for home, work and leisure environments, safely powering home appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop thanks to clear, intuitive controls. MASE EA 30 GH is equipped with a honda GX160 gasoline engine. They are very reliable engines that provide efficient combustion and **low fuel consumption**. The engines with which the generators are equipped are also equipped with a protection system that causes the engine to stop if the oil level is too low.

MASE EA 30 GH is a machine for stationary use, before commissioning you must first secure the generator firmly to the ground. MASE EA 30 GH power generators are equipped with 3 liter reservoir with a large cap that is convenient to unscrew even with work gloves

MASE EA 30 GH has an all-steel structure and a large metal tank. The generator guarantees an efficient and silent operation thanks to the Honda GX160 engine which allows to deliver a maximum power of 2.4KW.

## TECHNICAL CHARACTERISTICS MASE EA 30 GH

Maximum power Single phase: 2.4 KW

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Engine: Honda GX160



Starting: Manual  
Consumption: 1.3 Lt/h at 75% load  
Length: 585 mm  
Width: 360 mm  
Height: 410 mm  
Weight: 42 Kg

Are you looking for a power generator with different characteristics? Here you can find the full range of products MASE or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 2.4  
Maximum power single phase (KVA): 3  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 x 230V SCHUKO  
Engine: Honda GX160, 4 stroke, OHV  
Engine rpm (rpm): 3000  
Ignition: Recoil  
Starting system: Manual  
Engine capacity (cm<sup>3</sup>): 163  
Number cylinders: 1  
Cooling: Air  
Alternator: Synchronous  
Fuel tank capacity (L): 3.6  
Consumption (L/h): 1.3 at 75% of the load  
Running time (h): 2.76 at 75% of the load  
Acoustic power: 95 dB(A)  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 585  
Width (mm): 360  
Height (mm): 410  
Dry weight (Kg): 42  
Silenced: No  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: No  
Engine manufacturer: Honda

