



# MASE FX 12/4 GH GENERATOR 11KVA SINGLE PHASE /THREE PHASE AVR STAGEV

Product price:

**4.875,00 € tax excluded**

## Product description:

MASE FX 12/4 GH GENERATOR 11KVA SINGLE / THREE-PHASE AVR STAGEV

MASE FX 12/4 GH is a three-phase generator equipped with a Gasoline engine Honda GX630 OHV Stage V, capable of delivering a maximum power of 11KVA.

The MASE FX 12/4 GH generator provides reliable energy for home, work and leisure environments, safely powering household appliances and other electronic devices.

The generator is easy to install and operate, just as simple as starting and stopping thanks to the clear and intuitive controls. MASE FX 12/4 GH is equipped with a Honda GX630 OHV petrol engine. They are very reliable engines that guarantee efficient combustion and **reduced fuel consumption**, are also equipped with a protection system that causes the engine to stop if the oil level is too low.

MASE FX 12/4 GH is a machine for stationary use, before starting it must first firmly fix the generator to the ground. The MASE FX 12/4 GH are equipped with **29-liter tank** with a large cap that is easy to unscrew even with work gloves

MASE FX 12/4 GH has a completely steel structure and a large metal tank. The generator guarantees efficient and silent operation thanks to the Honda GX630 OHV which allows to deliver a maximum power of 11 KVA.

The generator is supplied with:

- Automatic shutdown due to low oil level
- Built-in 12 V battery
- 1 three-phase CEE socket 16 A, 400 V - 50 Hz protected by switch magnetothermic switch
- 1 single-phase CEE socket 16 A, 230 V - 50 Hz protected by a magnetothermic switch



- RCD switch
- Voltmeter
- Hour counter
- Hook central lifting

#### TECHNICAL CHARACTERISTICS MASE FX 12/4 GH

Phase type: Single-phase / Three-phase  
Maximum singlephase power: 4 KVA / 3.2 KW  
Singlephase continuous use power: 3.6 KVA / 2.8 KW  
Threephase maximum power : 11 KVA / 8.8 KW  
Continuous use power Threephase: 10 KVA / 8 KW  
Fuel: Gasoline  
Voltage: 230 V / 400 V  
Frequency: 50 Hz  
Engine: Honda GX630 OHV  
Emissions standard: StageV  
Engine revolutions: 3000 rpm  
Engine displacement: 688 cm<sup>3</sup>  
Cooling: Air  
Starting: Electric  
Voltage regulator: AVR  
Tank capacity: 29 l  
Consumption: 4.5 Lt / h at 75% of the load  
Sound Pressure: 98 dB (73 dB at 7 m)  
Protection class: IP 23  
Length: 940 mm  
Width: 488 mm  
Height: 823 mm  
Weight: 148 Kg

Are you looking for a generator with different characteristics? [HERE](#) you can find the full range of MASE products or other brands specialized in the sector

The images and technical data are not binding and may be subject to revisions by the supplier.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 3.2  
Continuous power single phase (KW): 2.8  
Maximum power single phase (KVA): 4  
Continuous power single phase (KVA): 3.6



---

Maximum power three phase (KW): 8.8  
Continuous power three phase (KW): 8  
Maximum power three phase (KVA): 11  
Continuous power three phase (KVA): 10  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 230V 16A 2P+T CE - 1 x 230V 32A 2P+T CE  
Engine: Honda GX630, 4 stroke, OHV  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 688  
Number cylinders: 2  
Cooling: Air  
Alternator: Synchronous  
Fuel tank capacity (L): 29  
Consumption (L/h): 6 at 75% of the load  
Running time (h): 4.83 at 75% of the load  
Acoustic power: 98 dB(A)  
Acoustic pressure: 73 dB(A) at 7 m  
Length (mm): 940  
Width (mm): 488  
Height (mm): 823  
Dry weight (Kg): 148  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Honda