



MASE FX 80 H/A GENERATOR 7 KVA SINGLE PHASE STAGE V

Product price:

3.225,00 € tax excluded

Product description:

MASE FX 80 H/A GENERATOR 7 KVA SINGLE PHASE STAGEV

MASE FX 80 H/A is a single-phase generator, equipped with a Honda GX390 **StageV** Gasoline engine, it delivers a maximum power of 7KW.

The MASE FX 80 H/A provides reliable power for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

Electric starting duct this unit is extremely easy to use and being very silent with its only 74 dB (A) of acoustic emission recorded at 7 meters it can also be used in urban centers, closed rooms or in any circumstance where a high Noise pollution could create inconvenience and problems.

The generator is easy to install and operate, just as simple are starting and stopping thanks to the clear and intuitive controls. MASE FX 80 H/A is equipped with a Honda GX390. They are very reliable engines that guarantee efficient combustion and **reduced fuel consumption**, they are also equipped with a protection system that causes the engine to stop if the oil level is too low.

STAGEV EMISSIONS REGULATION

MASE FX 80 H/A is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

Technical characteristics of MASE FX 80 H/A



Type of phase: Single-phase
Continuous power: 6 KVA / 4.8 KW
Maximum power: 7 KVA / 5.6 KW
VAC voltage: 230 V
Frequency (Hz): 50
Voltage regulator: Capacitor (AVR Optional)
Starting panel: Electric
Engine: Honda GX390
Emissions standard: StageV
Revolutions per minute: 3000 rpm
Fuel: Gasoline
Sockets panel: 1 x CEE 16A 230V / 1 x CEE 32A 230V
Tank capacity: 6.1 l
Autonomy: 1.8 h at 75% of the load
Consumption: 3.3 l / h at 75% of the load
Acoustic pressure: 74 dB (A) @ 7 m
Length: 725 mm
Width: 515 mm
Height: 585 mm
Net weight: 93 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to MASE generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Product features:

Phase: Single phase
Maximum power single phase (KW): 5.6
Continuous power single phase (KW): 4.8
Maximum power single phase (KVA): 7
Continuous power single phase (KVA): 6
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x CEE 16A 230V / 1 x CEE 32A 230V
Engine: Honda GX390, 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 389
Number cylinders: 1

Cooling: Air
Alternator: Synchronous
Fuel tank capacity (L): 6.1
Consumption (L/h): 3.3 at 75% of the load
Running time (h): 1.8 at 75% load
Acoustic power: 99 dB(A)
Acoustic pressure: 74 dB(A) at 7 m
Length (mm): 725
Width (mm): 515
Height (mm): 585
Dry weight (Kg): 93
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Honda