



# MASE PD 40 Y GENERATOR 4,3KVA SINGLE PHASE STAGEV

Product price:

**3.300,00 € tax excluded**

## Product description:

MASE PD 40 Y GENERATOR 4,3KVA SINGLE PHASE STAGEV

MASE PD 40 Y is a single-phase generator equipped with a diesel-supplied Yanmar L70V **StageV** engine, deliver a maximum power of 4,3KVA, complete with capacitor voltage regulator ( **AVR optional** ).

The generator is equipped with an electric start and has a low fuel consumption, in fact it consumes only 1 liters / hour at 75% of the load for an autonomy of up to 3.5 hours of operation.

MASE PD 40 Y provides reliable power for home, business and leisure environments Safely powering home appliances and other electronic devices Power solution for outdoor parties. Extremely practical sockets and controls make starting and operating easier, making these operations extremely simple and fast.

MASE PD 40 Y is equipped with a completely steel structure and a tank with a maximum capacity of 3.5 liters. The MASE PD 40 Y guarantees efficient and silent operation thanks to the Yanmar L70V StageV engine .

## STAGEV EMISSIONS REGULATION

With the abbreviation STAGEV, the guidelines and the limits of the gas emissions of the engines are defined. The legislation is respected through the installation of special anti-particulate filters, but an indispensable condition for the filter to work properly is that the generating set works at its design temperature.

## TECHNICAL CHARACTERISTICS OF MASE PD 40 Y

Type of phase: Single-phase

Continuous power: 3.5 KVA / 2.8 KW

Maximum power: 4.3 KVA / 3.4 KW  
VAC voltage: 230 V  
Frequency (Hz ): 50  
Voltage regulator: Capacitor (AVR Optional)  
Ignition panel: Electric  
Engine: Yanmar L70V  
Emissions standard: Stage V  
Revolutions per minute: 3000 rpm  
Fuel: Diesel  
Socket panel: 2 x CEE 16A 230V  
Tank capacity: 3.5 l  
Autonomy: 3.5 h at 75% of load  
Consumption: 1 l / h at 75% load  
Acoustic pressure: 74 dB (A) @ 7 m  
Length: 725 mm  
Width: 515 mm  
Height: 585 mm  
Net weight: 87 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to MASE generators and other specialized brands.

Non-binding images and technical data.

### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 3.4  
Continuous power single phase (KW): 2.8  
Maximum power single phase (KVA): 4.3  
Continuous power single phase (KVA): 3.5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 x 230V 16A CEE  
Engine: Yanmar L70AE, 4 stroke  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 320  
Number cylinders: 1  
Cooling: Air  
Alternator: Synchronous



---

Fuel tank capacity (L): 3.5  
Consumption (L/h): 1 at 75% of the load  
Running time (h): 3.5 at 75% of the load / 2.6 at 100% of the load  
Acoustic power: 99 dB(A)  
Acoustic pressure: 74 dB(A) at 7 m  
Length (mm): 725  
Width (mm): 515  
Height (mm): 585  
Dry weight (Kg): 87  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Yanmar

