



MASE PD 10 S GENERATOR 9,3KVA SINGLE PHASE STAGEV



Product price:

6.750,00 € tax excluded

Product description:

MASE PD 10 S GENERATOR 9,3KVA SINGLE PHASE STAGEV

MASE PD 10 S is a singlephase generator equipped with a Lombardini 25LD330 / 2 **StageV** diesel-powered engine, complete with condenser voltage regulator (**AVR optional**).

The generator is equipped with an electric start and has a low fuel consumption, in fact it consumes only 1.5 liters / hour at 75% of the load for an autonomy of up to 7 hours of operation.

The MASE PD 10 S is equipped with a soundproofed cabin, made of bent and electro-welded steel, with protection class IP23 and which can be opened in two sections. This cabin allows an incredible reduction of noise pollution, up to obtaining an acoustic pressure of only 72 dB (A) recorded at a distance of 7 meters.

ATS AUTOMATIC TRANSFER UNIT PREPARATION

The generator is set up for the use of an automatic ATS panel. Thanks to which you will no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the genset and will allow you to continue your business without losing your work data.

STAGEV EMISSIONS REGULATION

The MASE PD 10 S is equipped with a "mobile" STAGEV motorization, as required by the 2016/1628 European Regulation. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the genset into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL CHARACTERISTICS OF MASE PD 10 S



Type of phase: Singlephase
Continuous singlephase power: 8.3 KVA / 6.7 KW
Maximum singlephase power: 9.3 KVA / 7.4 KW
VAC voltage: 230 V
Frequency (Hz): 50
Voltage regulator: Capacitor (AVR Optional)
Starting panel: Electric
Engine: Lombardini 25LD330 / 2
Emissions standard: StageV
Revolutions per minute: 3000 rpm
Power supply: Diesel
Socket panel: 1 x CEE 16A 230V / 1 x CEE 32A 230V
Tank capacity: 10.5 l
Autonomy: 4.7 h at 75% of the load Consumption: 2.2 l / h at 75% of the load
Acoustic pressure: 72 dB (A) @ 7 m
Length: 1000 mm
Width: 560 mm
Height : 730 mm
Net weight: 190 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to MASE generators and other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase
Maximum power single phase (KW): 7.4
Continuous power single phase (KW): 6.7
Maximum power single phase (KVA): 9.5
Continuous power single phase (KVA): 8.3
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A 2P+T CE - 1 x 230V 32A 2P+T CE
Engine: Lombardini 25LD330.2, 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 654
Number cylinders: 2
Cooling: Air

Alternator: Synchronous
Fuel tank capacity (L): 10.5
Consumption (L/h): 2.2 at 75% of the load
Running time (h): 4.7 at 75 % of load
Acoustic power: 97 dB(A)
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 1000
Width (mm): 560
Height (mm): 715
Dry weight (Kg): 190
Silenced: Yes
Super silenced: No
ATS Switch device : Optional
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Lombardini