



# MASE MPV 16 BA



## Product description:

OUT OF PRODUCTION

Single-phase maximum power: 11 KW  
Three-phase maximum power: 12.8 KW  
Three-phase continuous use power: 12 KW  
Fuel: Diesel  
Voltage: 230 V / 400 V  
Frequency: 50 Hz  
Engine: Yanmar 3TNV88  
Starting: Electric  
Consumption: 2.5 Lt / h at 75% of the load  
Length: 1750 mm  
Width: 800 mm  
Height: 900 mm  
Weight: 600 Kg  
Compound

## Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 11  
Maximum power single phase (KVA): 11  
Maximum power three phase (KW): 12.8  
Continuous power three phase (KW): 12  
Maximum power three phase (KVA): 16  
Continuous power three phase (KVA): 15  
Fuel: Diesel



---

Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 2 x 230V 16A CE  
Engine: Yanmar 3TNV88, 4 stroke  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1642  
Number cylinders: 3  
Oil capacity (L): 6.7  
Cooling: Water  
Inyección : Direct  
Alternator: Synchronous, self-excited  
Poles: 4  
Lubrication: Forced  
Fuel tank capacity (L): 50  
Consumption (L/h): 2.5 at 75% of the load  
Running time (h): 20 at 75% of the load  
Acoustic power: 94 dB(A)  
Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 1750  
Height (mm): 900  
Dry weight (Kg): 600  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: Compound  
Engine manufacturer: Yanmar