MASE MPV 22 BA



Product description:

Ø.

OUT OF PRODUCTION

Single-phase maximum power: 13.5 KW Three-phase maximum power: 17.6 KW Three-phase continuous use power: 16 KW Fuel: Diesel Voltage: 230 V / 400 V Frequency: 50 Hz Engine: Yanmar 3TNV88 Starting: Electric Consumption: 2.5 Lt / h at 75% of the load Length: 1750 mm Width: 800 mm Height: 900 mm Weight: 600 Kg Compound

Product features:

Phase: Single phase / Three phase Maximum power single phase (KW): 13.5 Maximum power single phase (KVA): 13.5 Maximum power three phase (KW): 17.6 Continuous power three phase (KW): 16 Maximum power three phase (KVA): 22 Continuous power three phase (KVA): 20 Fuel: Diesel



Frequency (Hz): 50 Voltage (V): 230 / 400 Sockets configuration: 2 x 230V 16A CE Engine: Yanmar 3TNV88, 4 stroke Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 2190 Number cylinders: 4 Oil capacity (L): 7.4 Cooling: Water Inyección : Direct Alternator: Synchronous self-excited, with brushes Poles: 4 Lubrication: Forced Fuel tank capacity (L): 50 Consumption (L/h): 2.5 at 75% of the load Running time (h): 20 at 75% of the load Acoustic power: 94 dB(A) Length (mm): 1750 Height (mm): 900 Dry weight (Kg): 600 Silenced: Yes Super silenced: Yes ATS Switch device : Optional Voltage regulator: Compound Engine manufacturer: Yanmar