



MASE MPV 44 BA



Product description:

OUT OF PRODUCTION

Three-phase maximum power: 35.2 KW
Three-phase continuous use power: 32 KW
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: Deutz BF4M2011
Starting: Electric
Consumption: 5.61 Lt / h at 75% of the load
Length: 1980 mm
Width: 860 mm
Height: 1090 mm
Weight: 915 Kg
AVR

Product features:

Phase: Three phase
Maximum power three phase (KW): 35.2
Continuous power three phase (KW): 32
Maximum power three phase (KVA): 44
Continuous power three phase (KVA): 40
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 2 x 230V 16A CE



Engine: Deutz BF4M2011, 4 stroke
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 3108
Number cylinders: 4
Oil capacity (L): 10
Cooling: Oil
Inyección : Direct
Alternator: Synchronous self-excited, brushless
Poles: 4
Lubrication: Forced
Fuel tank capacity (L): 50
Consumption (L/h): 5.61 at 75% of the load
Running time (h): 8.9 at 75% of the load
Acoustic power: 95 dB(A)
Acoustic pressure: 70 dB(A) at 7 m
Length (mm): 1980
Width (mm): 860
Height (mm): 1090
Dry weight (Kg): 915
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Deutz