



## MASE VOYAGER 16 DM GENERATOR 19 KVA VEHICLE SINGLE-PHASE AVR STAGEV

**Product price:** 

19.162,50 € tax excluded

## **Product description:**

MASE VOYAGER 16 DM GENERATOR 19 KVA VEHICLE SINGLE-PHASE AVR STAGEV

MASE VOYAGER 16 DM single-phase vehicle generator with diesel-powered Yanmar 4TNV88 engine **StageV** delivers a power of 19KVA, **complete with AVR voltage regulator**.

The MASE VOYAGER 16 DM vehicle generator is equipped with a soundproofing cabin that makes it super silenced, with a sound emission of 62dB (A) at a distance of 7 m. The painted aluminum soundproof booth is extremely light and highly resistant to external agents.

The soundproof cabin allows easy access for maintenance of the fuel and lubrication systems, the water pump, the air filter, the oil filter and the fuel.

MASE VOYAGER 16 DM is equipped with a ComAp InteliNano control unit that allows you to control and verify all the main functions of the unit and, if necessary, will report any failure or error in the operation of the machine.

## AVR VOLTAGE REGULATOR

The purpose of the regulator in a power source is to keep the output stable. And if its operation is very simple when resistive loads are supplied, the situation is more complex in the case of mainly inductive loads: the delayed phase-shifted current contrasts the inductor magnetic field, causing a voltage drop at the alternator output terminals.; to compensate for the phenomenon, the AVR intervenes automatically by increasing the excitation current, until the output returns to the nominal value.

TECHNICAL FEATURES MASE VOYAGER 16 DM:





Phase Type: Single Phase

Maximum Power: 19 KVA / 15.2 KW Continuous Power: 17.25 KVA / 13.9 KW

Fuel: Diesel Voltage: 230 V Frequency: 50 Hz

Engine: Yanmar 4TNV88 Mechanical power: 24.1 Hp Number of cylinders: 4

Number of cylinders: 4 Displacement: 2190 cc Engine rpm: 1500 rpm

Emissions standard: StageV

Consumption: 3.5 I / h at 75% load Acoustic pressure: 62 dBA @ 7 m

Voltage regulator: AVR

Length: 1570 mm Width: 650 mm Height: 810 mm Weight: 550 Kg

Are you looking for a product with different technical characteristics? HERE you can find the area dedicated to MASE vehicle generators or other specialized brands.

Non-binding images and technical data.

## **Product features:**

Phase: Single phase

Maximum power single phase (KW): 15.2 Continuous power single phase (KW): 13.9 Maximum power single phase (KVA): 19 Continuous power single phase (KVA): 17.25

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Engine: Yanmar 4TNV88, 4 stroke naturally aspirated

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500 Starting system: Electric Engine capacity (cm³): 2190

Number cylinders: 4 Oil capacity (L): 7.4 Cooling: Water





Alternator: Sincrono, autoeccitato, autoregolato, senza spazzole

Poles: 4

Consumption (L/h): 3.5 to 75 % of load Acoustic pressure: 62 dB(A) at 7 m

Length (mm): 1570 Width (mm): 650 Height (mm): 810 Dry weight (Kg): 550

Inverter: No AVR: Yes

Compound: No Silenced: Yes

Super silenced: Yes Voltage regulator: AVR

Engine manufacturer: Yanmar

