

# GENSET MPM 15/400 I-K STAGE V



**Product price:**

**9.272,00 € tax excluded**

## Product description:

The MPM range has been designed to meet the needs of those who need motor welding machines for highly professional applications. This result has been obtained mainly thanks to the peculiar characteristics of the GenSet asynchronous alternator: versatility, reliability and efficiency.

The attention paid by GenSet to the different needs of users of motor welding machines in every part of the world and in every environmental condition, has resulted in the development of a complete range in terms of:

- type of motorization;
- different levels of soundproofing;
- variety of welding processes that can be carried out;
- number of accessories available.

The image is purely indicative.

## Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 8

Maximum power single phase (KVA): 10

Maximum power three phase (KW): 12

Maximum power three phase (KVA): 15

Fuel: Diesel

Voltage (V): 230 / 400

Sockets configuration: 1 three-phase CEE 32 A+ socket 2 single-phase CEE 32 A sockets

Engine: Kubota D1105-E

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

---

Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1123  
Number cylinders: 3  
Cooling: Water  
Alternator: Asynchronous, self-excited and self-protected  
Welding current (A): 370 A at 35% - 350 A at 60%  
Open circuit voltage (V): 70  
Fuel tank capacity (L): 60  
Consumption (L/h): 4.9 at 75% of the load  
Running time (h): 12.23  
Acoustic power: 98 dB(A)  
Acoustic pressure: 73 dB(A) at 7 m  
Length (mm): 1600  
Width (mm): 840  
Height (mm): 1000  
Dry weight (Kg): 565  
Inverter: No  
AVR: No  
Compound: No  
Silenced: Yes  
Super silenced: Yes