

# TECNOGEN H3000



## Product description:

### TECNOGEN H3000

Generating sets available in both single-phase and three-phase versions, with powers from 2.3 to 21 kVA MAX, equipped with gasoline or diesel engines, air-cooled, 3000 rpm, electric and/or manual starting with recoil starter. Compact, simplified and economical, they boast an excellent price/performance/size and weight ratio.

Easily transportable thanks to the reduced overall dimensions due to an essential equipment, they are suitable for all those who need an economic source of energy, however assembled with first-rate components that guarantee absolute reliability. The petrol versions of the COMPACT line, thanks to the latest generation Honda engines, fall within the parameters of the noise directive 2000/14/EC.

The image is purely indicative.

## Product features:

Phase: Single phase

Maximum power single phase (KW): 2.2

Maximum power single phase (KVA): 2.8

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: HONDA GC160

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Manual

---

Engine capacity (cm<sup>3</sup>): 163  
Number cylinders: 1  
Cooling: Air  
Fuel tank capacity (L): 3.6  
Consumption (L/h): 0.9  
Running time (h): 4  
Acoustic power: 96 dB(A)  
Length (mm): 590  
Width (mm): 390  
Height (mm): 380  
Dry weight (Kg): 36  
Silenced: No  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: No  
Engine manufacturer: Honda