

TECNOGEN H 8000E/A WITH SEPARATE AUTOMATIC PANEL



Product description:

TECNOGEN H 8000E / A WITH SEPARATE AUTOMATIC PANEL

Generating sets available in both single-phase and three-phase versions, with powers from 2.3 to 21 kVA MAX, equipped with gasoline or diesel engines, air-cooled, 3000 rpm, with electric and / or manual starting with recoil . Compact, simplified and economical, they boast an excellent price / performance / size and weight ratio.

Easily transportable thanks to the reduced dimensions due to an essential set-up, they are suitable for all those who need an economic source of energy. assembled with first-rate components that guarantee absolute reliability. Thanks to the latest generation Honda engines, the petrol versions of the COMPACT line fall within the parameters of the noise directive 2000/14 / EC.

The image is purely indicative.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5.8

Maximum power single phase (KVA): 7.2

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: HONDA GC160

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 389

Number cylinders: 1

Cooling: Air
Fuel tank capacity (L): 6.5
Consumption (L/h): 1.9
Running time (h): 3.42
Acoustic power: 96 dB(A)
Length (mm): 780
Width (mm): 520
Height (mm): 560
Dry weight (Kg): 80
Silenced: No
Super silenced: No
ATS Switch device : Yes
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Honda