

# TECNOGEN H15000TELX

Product price:

**3.546,00 € tax excluded**



## Product description:

Generating sets available in both single-phase and three-phase versions, with powers from 4.5 to 13.3 kVA MAX, equipped with gasoline or diesel engines, air-cooled, 3000 rpm, with electric and / or manual start with self-winding. Characterized by a particularly sophisticated design, they also stand out in terms of the set-up. In fact, they have a complete coverage of the upper part consisting of a sturdy sheet metal roof with central lifting point, a 20 Lt tank in polyethylene and an electrical panel positioned in a special protected compartment, separated from the motor / alternator unit and therefore exempt. from vibrations, equipped with hour meter and magnetothermic / differential switch. Thanks to their features and the latest generation Honda engines, which allow the petrol versions to fall within the parameters of the noise directive 2000/14 / EC, the LX series generator sets are the ideal solution for operators who need generators equipped with a professional set-up while remaining in the range of non-soundproofed machines.

The image is purely indicative.

## Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 3  
Maximum power single phase (KVA): 3.8  
Maximum power three phase (KW): 10.4  
Maximum power three phase (KVA): 13  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: HONDA GC160  
Emissions Regulations: Stage 5

---

Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 688  
Number cylinders: 2  
Cooling: Air  
Fuel tank capacity (L): 20  
Consumption (L/h): 7  
Running time (h): 2.8  
Acoustic power: 98 dB(A)  
Length (mm): 990  
Width (mm): 550  
Height (mm): 670  
Dry weight (Kg): 133  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: No  
Engine manufacturer: Honda