



# TECNOGEN H2700



## Product description:

### TECNOGEN PK150T GENERATOR SET

TECNOGEN PK150T GENSET is a three-phase genset designed to provide electrical in the event of a blackout or for professional applications. It is a versatile model, suitable for a variety of applications, including:

**Emergency supply:** In the event of a blackout, the TECNOGEN PK150T can supply support to homes, offices and other buildings.

**Professional applications:** The TECNOGEN PK150T is ideal for professional applications requiring a reliable and powerful source, such as construction sites, industry and business.

**Camping:** The TECNOGEN PK150T can be used to power camping equipment such as lights, refrigerators and televisions.

The TECNOGEN GENSET PK150T has a number of features that make it a high-quality product, including:

**Diesel engine:** The diesel engine is a reliable and powerful engine, providing high autonomy and low fuel consumption.

**AVR voltage regulator:** The AVR voltage regulator guarantees a stable and constant voltage, regardless of variations in the load or input voltage.

## Technical characteristics TECNOGEN PK150T GENSET:

Maximum three-phase : 120 KW

Maximum three-phase : 150 KVA

Fuel: Diesel



Voltage: 400V  
Engine: Perkins 1006TAG  
Starter: Electric  
Length: 2300 mm  
Width: 780 mm  
Height: 1440 mm  
Weight: 1250 kg

The TECNOGEN PK150T diesel engine is a Perkins 1006TAG, rated at 121 kW. The generator has a rated power of 120 kW.

On a construction site it can be used to construction equipment such as concrete mixers, cranes and compressors. For example, the genset can be used to power many situations.

In an industry, the genset can be used to power industrial machinery, such as presses, ovens and robots. For example, the genset can be used to power a press for example.

The TECNOGEN PK150T genset is a reliable and powerful genset.

If you are looking for a product similar to or with similar features click [HERE](#).

Images purely indicative.

#### **Product features:**

Phase: Three phase  
Maximum power three phase (KW): 120  
Maximum power three phase (KVA): 150  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 400  
Engine: HONDA GC160  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 5990  
Number cylinders: 6  
Cooling: Water  
Fuel tank capacity (L): 189  
Consumption (L/h): 20.8  
Running time (h): 9  
Length (mm): 2300

---

Width (mm): 780  
Height (mm): 1440  
Dry weight (Kg): 1250  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: No  
Engine manufacturer: Perkins