

TECNOGEN H8000LX-TF Lighting Tower with 7.2 kVA Single Phase Genset

Product description:

Ø.

The Tecnogen MT Series light towers, extremely versatile in terms of size and fittings, can be managed by a single operator, also thanks to special locks that drastically reduce the minimum height encumbrance of the telescopic pole, making it easy to move the units themselves without complicated repositioning operations. The equipment includes a 4- or 5-outlet headlight column made of anodised aluminium alloy or steel galvanised, depending on the model, with a height of 5/7/9 metres, complete with support with 4 adjustable halogen spotlights 500 or 1000 watts each. Available configurations include series generating sets "LX" from 4.5 to 7.5 kVA max (petrol or diesel), "SX" series (silenced), 4.6 to 6.4 kVA max and Enermax series 14.5 to 44 kVA max. The series LX and SX are equipped with a trolley for manual movements, also on rugged terrain, with lockable handles and pneumatic wheels mounted on bearings. The standard equipment also includes 4 removable outrigger feet and Individually adjustable to ensure the flat stability of the unit lighting, thus making it possible to operate safely with the column of headlamps in extension. The Tecnogen MT series light towers are ideal for operators who need a source of energy and lighting.

Non-binding images and technical data.

Product features:

Phase: Single phase Maximum power single phase (KW): 5.8 Maximum power single phase (KVA): 7.2 Fuel: Gasoline

R

Frequency (Hz): 50 Voltage (V): 230 Engine: HONDA GC160 Engine rpm (rpm): 3000 Starting system: Manual Engine capacity (cm³): 389 Number cylinders: 1 Cooling: Air Type of lamps: Halogen Lamps: 4 x 500 W Total lumens (Lm): 35000 Lifting System: Manual lifting system Maximum height (m): 5.5 Lenght closed (mm): 1040 Width closed (mm): 820 Height closed (mm): 1800 Transportability: Wheels and handles Fuel tank capacity (L): 20 Consumption (L/h): 0,8 al 75% del carico Running time (h): 10.5 Acoustic power: 96 dB(A) Dry weight (Kg): 140 Inverter: No AVR: No Compound: No Silenced: No Super silenced: No Engine manufacturer: Honda

Ø.