

TECNOGEN SH180E



Product description:

TECNOGEN SH180E MOTORWELDING 4,5KVA

TECNOGEN SH180E features a rugged frame to protect a powerful HONDA GX270 motor capable of delivering 4.5KVA single-phase power with a maximum load consumption of 2.4 L/h.

TECNOGEN SH180E is with electric start with 12V battery supplied with acid or manual with self-winding, with control panel QM115 composed of singlephase CEE socket 2P+T 16A, thermal protection, singlephase Schuko socket 2P+T 16A.

TECHNICAL FEATURES TECNOGEN SH180E

Soldering at 60%: 170

Maximum single-phase power: 4.5 KVA

Fuel: Gasoline

Voltage: 230V

Engine: Honda GX270

Boosting: Electric

Length: 780 mm

Width: 520 mm

Height: 560 mm

Weight: 80 Kg

Are you looking for a motorwelding with different technical characteristics? Here you can find the full range of TECNOGEN and other specialized brands.

The images are purely indicative.



Product features:

Phase: Single phase

Maximum power single phase (KVA): 4.5

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: HONDA GC160

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 160

Number cylinders: 1

Cooling: Air

Welding current (A): 180 al 35% - 170 al 60%

Fuel tank capacity (L): 2

Consumption (L/h): 0,8 al 75% del carico

Running time (h): 2,5

Acoustic power: 95 dB(A)

Length (mm): 78

Width (mm): 52

Height (mm): 56

Dry weight (Kg): 27

Inverter: No

AVR: No

Compound: No

Silenced: Yes

Super silenced: No

