

# TECNOGEN SH220TE



## Product description:

TECNOGEN SH220TE MOTORWELDER 7,5KVA

TECNOGEN SH220TE is a motorwelder equipped with a Honda GX390 gasoline engine, capable of delivering a three-phase power of 7.5KVA.

TECNOGEN SH220TE is a motorwelder with a welding current of 120 to 160A max., equipped with an air-cooled, 3600 rpm max. gasoline engine in an open frame complete with recoil starter.

TECNOGEN SH220TE is equipped with a robust frame to protect a powerful HONDA GX390 motor capable of delivering a three-phase power of 7.5KVA with a maximum load consumption of 2.4 L/h.

TECNOGEN SH220TE is equipped with electric start with 12V battery supplied with acid or manual with self-winding, with QM115 control panel composed of three-phase EEC socket 2P+E 16A, thermal protection, three-phase Schuko socket 2P+E 16A.

## Technical characteristics TECNOGEN SH220TE

Soldering at 60%: 170

Maximum three-phase power: 7.5KVA

Fuel: Gasoline

Voltage: 400V

Engine: Honda GX390

Boosting: Electric

Length: 920 mm

Width: 520 mm

Height: 660 mm

Weight: 80 Kg



Are you looking for a motorwelding with different technical characteristics? Here you can find the full range of TECNOGEN and other specialized brands.

The images are purely indicative.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KVA): 3.5  
Maximum power three phase (KVA): 7.5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: HONDA GC160  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 160  
Number cylinders: 1  
Cooling: Air  
Welding current (A): 180 al 35% - 170 al 60%  
Fuel tank capacity (L): 2  
Consumption (L/h): 0,8 al 75% del carico  
Running time (h): 2,5  
Acoustic power: 95 dB(A)  
Length (mm): 78  
Width (mm): 52  
Height (mm): 56  
Dry weight (Kg): 27  
Inverter: No  
AVR: No  
Compound: No  
Silenced: Yes  
Super silenced: No

