



# HONDA ECT 7000 Petrol Single / Three Phase Generator max. 7 kW

## Product description:

When it comes to a generator on a construction site, you don't want to cut corners on quality. Always choose a Honda for those jobs that need to be done with minimum fuss. They're tough and always ready to go.

## Plenty of energy

Simplicity and cost effectiveness go hand in hand with a condenser/inductive type EC generator. The power produced is perfect for resistive loads like power drills, circular saws and concrete breakers.

## LET'S START WORK

Just fire it up and forget it.

Quick and easy: the accessible ergonomic fuel filler cap is right where you need it – on top. Practical sockets and controls make starting and running the generator quick and simple. Just start it and let it get on with the job, because the unique Oil Alert™ will automatically switch off the ignition if the oil drops below a safe level. It's as safe as safe can be.

## Smooth running

Honda has built an engine mount system into the durable steel frame. These rubber shock absorbers are positioned either side of the engine at 45° and significantly reduce the engine vibration of an already quiet machine.

The photos are for illustrative purpose only.



**Product features:**

Phase: Single phase / Three phase

Maximum power single phase (KW): 4

Continuous power single phase (KW): 3.6

Maximum power single phase (KVA): 5

Continuous power single phase (KVA): 4.2

Maximum power three phase (KW): 7

Continuous power three phase (KW): 6.5

Maximum power three phase (KVA): 8.75

Continuous power three phase (KVA): 8.12

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V CEE - 2 x 230V SCHUKO

Engine: Honda GX390 T1, 4 stroke, OHV

Engine rpm (rpm): 3000

Ignition: Transistorized

Starting system: Manual

Engine capacity (cm<sup>3</sup>): 389

Number cylinders: 1

Oil capacity (L): 1.1

Cooling: Air

Alternator: Tripolar

Bore x stroke (mm): 88 x 64

Fuel tank capacity (L): 6.2

Consumption (L/h): 2.75

Running time (h): 2.25

Acoustic power: 97 dB(A)

Acoustic pressure: 86 dB(A)

Length (mm): 800

Width (mm): 550

Height (mm): 540

Dry weight (Kg): 77

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Honda

Video: V0JyzKGrpJE

