



# TECNOGEN SD200YTE



## Product description:

TECNOGEN SD200YTE MOTORWALKER 6,3KVA

TECNOGEN SD200YTE is a motorwelder equipped with a Yanmar L100AE gasoline engine, capable of delivering a three-phase power of 6.3KVA.

TECNOGEN SD200YTE is a motorwelder with a welding current from 120 to 160A max., with a 3600 rpm max. air-cooled gasoline engine, in an open frame complete with recoil starter.

TECNOGEN SD200YTE is equipped with a sturdy frame to protect a powerful Yanmar L100AE motor capable of delivering a three-phase power of 6,3KVA with a maximum load consumption of 2.4 L/h.

TECNOGEN SD210LTE is with electric start with 12V battery supplied with acid or manual with self-winding, with QM115 control panel composed of three-phase EEC socket 2P+E 16A, thermal protection, three-phase Schuko socket 2P+E 16A.

Technical characteristics TECNOGEN SD200YTE

Soldering at 60%: 170

Maximum three-phase power: 6.3 KVA

Fuel: Diesel

Voltage: 400V

Engine: Yanmar L100AE

Boosting: Electric

Length: 920 mm

Width: 520 mm

Height: 660 mm

Weight: 115 Kg



Are you looking for a motorwelding with different technical characteristics? Here you can find the full range of TECNOGEN and other specialized brands.

The images are purely indicative.

**Product features:**

Phase: Three phase

Maximum power single phase (KVA): 5.5

Maximum power three phase (KVA): 7

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: HONDA GC160

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 160

Number cylinders: 1

Cooling: Air

Welding current (A): 180 al 35% - 170 al 60%

Fuel tank capacity (L): 2

Consumption (L/h): 0,8 al 75% del carico

Running time (h): 2,5

Length (mm): 78

Width (mm): 52

Height (mm): 56

Dry weight (Kg): 27

Inverter: No

AVR: No

Compound: No

Silenced: Yes

Super silenced: No