

# GREEN POWER GP22A- PW-N-C OPEN



Product price:

**5.664,00 € tax excluded**

## Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 17.6

Continuous power three phase (KW): 16

Maximum power three phase (KVA): 22

Continuous power three phase (KVA): 20

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: PERKINS 404A-22G1, 4 stroke naturally aspirated

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 2216



---

Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water  
Alternator: Linz E1S13MF/4, synchronous, with brushes  
Poles: 4  
Fuel tank capacity (L): 60  
Consumption (L/h): 4 at 75% of the load  
Running time (h): 15  
Length (mm): 1500  
Width (mm): 700  
Height (mm): 1020  
Dry weight (Kg): 530  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: Compound

