



TECNOGEN LD22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Product description:

TECNOGEN LD22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Super-silenced diesel generator sets with electric start, air-cooled, 3000 rpm, available in both single-phase and three-phase versions, with powers from 6.3 to 21 kVA MAX. Extremely small in size, the carpentry of this series boast a particular configuration that facilitates routine maintenance operations. The excellent performance / size ratio and the high level of soundproofing make these generators the ideal solution for limited spaces in which it is necessary to operate with the utmost silence (vans set up for road maintenance, mobile workshops, etc.). Easy and versatile to position, they are also suitable for installations with automatic intervention electrical panel, in full compliance with current regulations.

The image is purely indicative.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 5.6
Maximum power single phase (KVA): 7
Maximum power three phase (KW): 16.8
Maximum power three phase (KVA): 21
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: HONDA GC160

Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 1248
Number cylinders: 2
Cooling: Air
Fuel tank capacity (L): 48
Consumption (L/h): 4.9 at 75% of the load
Running time (h): 9.7 at 75% of the load
Acoustic power: 96 dB(A)
Length (mm): 1450
Width (mm): 800
Height (mm): 1060
Dry weight (Kg): 400
Silenced: No
Super silenced: Yes
ATS Switch device : Yes
Voltage regulator: Compound
Engine manufacturer: Lombardini