



# HONDA Outboard BF 20 LHU 56 cm Shaft With Tiller 14.9 kW 350 cm<sup>3</sup>

**Product price:**

**2.850,00 € tax excluded**

## **Product description:**

HONDA OUTBOARD BF20DK2 LHU SHAFT 43 CM

Honda BF20DK2 LHU is an incredibly practical and portable 15 or 20 horsepower outboard engine with well-placed retractable handles. They are perfect for any boat that needs power in a small size.

The engine that comes with the Honda BF20DK2 4-stroke stays quiet both when starting and when increasing its power; they are so quiet that you can take them to their full power, without having to raise your voice to speak. Honda's exclusive vibration-absorbing rubber mounting system gives a great impression of smoothness.

These Honda 350 cm<sup>3</sup> 4-stroke engines are easy to start, thanks to the decompression system and PGM-IG programmed ignition. This ignition system precisely delivers the right amount of air/fuel mixture to the twin cylinders. The engine, even when cold, is able to deliver all the power required.

Honda BF20DK2 outboards have an automatic decompression system that makes starting easier. This makes the engine easier to start in the initial pull in the case of manual starting and places much less strain on the battery in the case of electric starting.

During forward travel, the Honda BF20DK2's propeller is driven normally through water, as with all marine engines. In the reverse direction, however, Honda engines make all the difference. This unique reverse exhaust system directs bubbles out of the propeller so it can "grip" the water. The result is immediate response and very precise control.

Honda BF20DK2 LHU with manual start is available in the version with electric start allow lifting and lowering, allowing you to adjust the trim of the boat to always get the best in performance and fuel efficiency. This also prevents damage to the propeller blades when the boat is close to rocks or shallow water.



Honda BF20DK2 LHU outboards have a reverse lever that allows you to change gears with your fingertips. Everything is much easier to use and better positioned than other outboards even for left-handed people. In addition, the soft-grip, twist-lock throttle grip minimizes operating effort, increasing handling.

Honda BF20DK2 LHU outboards are available with rudder and remote control options. The remote control option displays warning lights for engine, oil pressure and overheating. It also generates an audible signal to get your attention in case anything happens while you're focusing on other tasks.

Honda BF20DK2 LHU is anodized the aluminum housing using Honda's patented "double seal" process. Then a layer of epoxy primer is applied before the silver gloss paint. As additional UV protection, a clear resin is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

#### TECHNICAL CHARACTERISTICS HONDA BF20DK2 LHU

Net Power (kW): 14.9

Net Power (Hp): 20

Displacement: 350 cm<sup>3</sup>

Shaft length: Long

Dry weight (Kg): 49.5

Starter: Electric / Manual

Ignition system: Electronic PGM-IG

Control type: Bar

Setup and engine lifting: Manual / Manual 5 positions

Transom height (mm): 563

Length (mm): 650

Width (mm): 350

Height (mm): 1240

Bore x stroke: 59 x 64 mm

Engine Brand: Honda

Engine Type: OHV, 4 stroke

Number of cylinders: 2

Speed at full throttle (rpm): 5000-6000

Cooling system: Water

Battery charge capacity (A): 6

Propeller Rotation: Standard

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the field.

Images are indicative only.



---

**Product features:**

Fuel: Gasoline

Engine: OHV, 4 stroke

Ignition: Electronic PGM-IG

Starting system: Manual / Electric

Engine capacity (cm<sup>3</sup>): 350

Number cylinders: 2

Cooling: Water (with thermostat)

Bore x stroke (mm): 59 x 64

Reduction ratio: 2.08

Rpm at full throttle (rpm): 5000 - 6000

Appearance and engine lifting: Manual / Manual 5 position

Transom height (mm): 563

Net power (kW): 14.9

Fuel tank capacity (L): 12

Length (mm): 650

Width (mm): 350

Height (mm): 1240

Dry weight (Kg): 49.5

Shaft Length: L

Controls: Tiller

