

HONDA BF 20 SHSU 43 cm Shaft With Tiller 14.9 kW 350 cm³

Product price:

2.868,85 € tax excluded

Product description:

HONDA OUTBOARD BF20DK2 SHSU SHAFT 43 CM

Honda BF20DK2 SHSU is an incredibly practical and portable 15 or 20 horsepower outboard engine with well-placed retractable handles. They are perfect for any boat that needs power in a small size.

The engine that comes with the Honda BF20DK2 4-stroke stays quiet both when starting and when increasing its power; they are so quiet that you can take them to their full power, without having to raise your voice to speak. Honda's exclusive vibration-absorbing rubber mounting system gives a great impression of smoothness.

Honda BF20DK2 outboards have an automatic decompression system that makes starting easier. This makes the engine easier to start in the initial pull in the case of manual start and places much less burden on the battery in the case of electric start.

During forward travel, the Honda BF20DK2's propeller is driven normally through water, as with all marine engines. In the reverse direction, however, Honda engines make all the difference. This unique reverse exhaust system directs bubbles out of the propeller so it can "grip" the water. The result is immediate response and very precise control.

Honda BF20DK2 SHSU with manual start is available in the version with electric start allow lifting and lowering, allowing you to adjust the trim of the boat to always get the best in performance and fuel efficiency. This also prevents damage to the propeller blades when the boat is close to rocks or shallow water.

Honda BF20DK2 SHSU outboards have a reverse lever that allows you to change gears with your fingertips. Everything is much easier to use and better positioned than other outboards even for left-handed people. In addition, the soft-grip, twist-lock throttle grip minimizes operating effort, increasing handling.

Honda BF20DK2 SHSU outboards are available with rudder and remote control options. The remote control option displays warning lights for engine, oil pressure and overheating. It also generates an audible signal to get your attention in case anything happens while you're focusing on other tasks.

Honda BF20DK2 SHSU is anodized the aluminum housing using Honda's patented "double seal" process. Then a layer of epoxy primer is applied before the silver gloss paint. As additional UV protection, a clear resin is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

TECHNICAL CHARACTERISTICS HONDA BF20DK2 SHSU

Net Power (kW): 14.9 Net Power (Hp): 20 Displacement: 350 cm³ Shank length: Short Dry weight (Kg): 49 Starter: Electric / Manual Ignition system: Electronic PGM-IG Type of control Bar Setup and engine lifting: Manual / Manual 5 positions Transom height (mm): 433 Length (mm): 650 Width (mm): 350 Height (mm): 1110 Bore x stroke: 59 x 64 mm **Engine Brand: Honda** Engine Type: OHV, 4 stroke Number of cylinders: 2 Speed at full throttle (rpm): 5000-6000 Cooling system: Water Battery charge capacity (A): 12 **Propeller Rotation: Standard**

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the field.

Images are indicative only.

Product features:

Fuel: Gasoline Engine: OHV, 4 stroke

PrestaShop

R

Ø.

Ignition: Electronic PGM-IG Starting system: Manual / Electric Engine capacity (cm³): 350 Number cylinders: 2 Cooling: Water (with thermostat) Bore x stroke (mm): 59 x 64 Reduction ratio: 2.08 Rpm at full throttle (rpm): 5000 - 6000 Appearance and engine lifting: Manual / Manual 5 position Transom height (mm): 433 Net power (kW): 14.9 Fuel tank capacity (L): 12 Length (mm): 650 Width (mm): 350 Height (mm): 1110 Dry weight (Kg): 49 Shaft Length: S **Controls: Tiller**



R