



# HONDA Outboard BF 20 LRU 56 cm Shaft With Remote 14.9 kW 350 cm<sup>3</sup>

**Product price:**

**3.270,00 € tax excluded**

## **Product description:**

HONDA OUTBOARD BF20DK2 LRU SHAFT 56 CM

Honda BF20DK2 LRU is an incredibly practical and portable 15 or 20 horsepower outboard engine with well-placed retractable handles. They are perfect for any boat that needs power in a small size.

The engine that comes with the Honda BF20DK2 4-stroke stays quiet both when starting and when increasing its power; they are so quiet that you can take them to their full power, without having to raise your voice to speak. Honda's unique vibration-absorbing rubber mounting system gives a great impression of smoothness.

During forward travel, the Honda BF20DK2's propeller is driven normally through the water, as with all marine engines. In the reverse direction, however, Honda engines make all the difference. This unique reverse exhaust system directs bubbles out of the propeller so it can "grip" the water. The result is immediate response and very precise control.

Honda BF20DK2 LRU with manual start is available in the version with electric start allow lifting and lowering, allowing you to adjust the trim of the boat to always get the best in performance and fuel efficiency. This also prevents damage to the propeller blades when the boat is close to rocks or shallow water.

Honda BF20DK2 LRU outboards have a reverse lever that lets you shift gears with your fingertips. Everything is much easier to use and better positioned than other outboards even for left-handed people. In addition, the soft-grip, twist-lock throttle grip minimizes operating effort, increasing handling.

Honda BF20DK2 LRU outboards are available with rudder and remote control options. The remote control option displays warning lights for engine, oil pressure and overheating. It also generates an audible signal to get your attention in case anything happens while you're focusing

on other tasks.

Honda BF20DK2 LRU is anodized the aluminum housing using Honda's patented "double seal" process. Then a layer of epoxy primer is applied before the silver gloss paint. As additional UV protection, a clear resin is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

#### TECHNICAL CHARACTERISTICS HONDA BF20DK2 LRU

Net Power (kW): 14.9  
Net Power (Hp): 20  
Displacement: 350 cm<sup>3</sup>  
Shaft length: Long  
Dry weight (Kg): 51  
Starter: Electric / Manual  
Ignition system: Electronic PGM-IG  
Type of control Remote  
Setup and engine lifting: Manual / Manual 5 positions  
Transom height (mm): 563  
Length (mm): 650  
Width (mm): 350  
Height (mm): 1240  
Bore x stroke: 59 x 64 mm  
Engine Brand: Honda  
Engine Type: OHV, 4 stroke  
Number of cylinders: 2  
Speed at full throttle (rpm): 5000-6000  
Cooling system: Water  
Battery charge capacity (A): 12  
Propeller Rotation: Standard

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the field.

Images are indicative only.

#### Product features:

Fuel: Gasoline  
Engine: OHV, 4 stroke  
Ignition: Electronic PGM-IG  
Starting system: Manual / Electric  
Engine capacity (cm<sup>3</sup>): 350

---

Number cylinders: 2  
Cooling: Water (with thermostat)  
Bore x stroke (mm): 59 x 64  
Reduction ratio: 2.08  
Rpm at full throttle (rpm): 5000 - 6000  
Appearance and engine lifting: Manual / Manual 5 position  
Transom height (mm): 563  
Net power (kW): 14.9  
Fuel tank capacity (L): 12  
Length (mm): 650  
Width (mm): 350  
Height (mm): 1240  
Dry weight (Kg): 51  
Shaft Length: L  
Controls: Remote