



HONDA Outboard BF 100AK1 LRTU Long Shaft With Tiller 73.6 kW 1496 cm³

Product price:

8.630,00 € tax excluded

Product description:

HONDA Outboard BF 100 LRTU Long Shaft Drive

Honda BF100AK1 LRTU are outboard engines perfect for professional use, they are reliable, compact and lightweight complete with PGM-Fi electronic fuel injection system.

Honda BF100AK1 LRTU 1.5-liter outboard engine has 16 valves and a single overhead cam. In addition, the PGM-Fi electronic injection system allows for easy starting, powerful acceleration and exceptionally low fuel consumption. The VTEC™ is also available on the Honda BF100AK1 LRTU. When combined with the ECOMo, it not only offers outstanding economy, but also remarkable high-rpm performance. These outboards are lightweight and compact, and with NMEA2000® connectivity, they're a big favorite with marine enthusiasts.

Honda BF100AK1 LRTU comes complete with a patented VTEC™ system, it's an efficient system that keeps fuel consumption down while delivering an exciting increase in power. First used on Honda's Formula One cars, it delivers increased power and torque at all engine speeds. In the Honda BF100AK1 LRTU works by using two different cams:

- 1) When the engine is running at low rotations, the valves are operated by a cam less aggressively ensuring low consumption and excellent performance.
- 2) When more power is desired, as the rotations increases to 4500 rpm, the VTEC™ hydraulically operates a cam with a higher lift profile. This keeps the valves open longer, getting more air into the combustion chamber to produce optimum power, like a Formula One race car. At this point, the outboard takes on a completely different personality that will be noticeable both to the ear and in performance.

Honda BF100AK1 LRTU features the BLAST™ Ready Start System, which gets the outboard up to speed in seconds. The BLAST™ (Boosted Low Speed Torque) delivers high torque even at low rotations by unleashing powerful thrust from startup. The ECU automatically advances the

ignition timing, while increasing the fuel-to-air ratio to give you more thrust from low rpm. This innovative technology patented for Honda 4-stroke outboards has become the benchmark in the design of these engines.

The Honda BF100AK1 LRTU dual-stage air induction works with a shuttle valve built into the Variable Air Intake (VAI) manifold. When fully open, this valve changes the resonance and airflow generating more torque at low rotations. When the throttle valve is fully open and rpm increases, the cooling valve closes and creates airflow directed to the outboard. This provides more power above 3500 rpm. Combined with the BLAST™, you get a disruptive effect.

The special ECOmo poor-blend combustion control system delivers significant fuel economy right through rotations and performance. Once up to speed, much less fuel is consumed. Maintaining this RPM and staying there gives the best results. Once you reach cruising speed, ECOmo automatically and intelligently adjusts the correct air/fuel ratio for that speed. Normally it comes into operation in the green zone (shown on the dial) or when the green Eco light comes on (in case you have multifunctional indicators). Therefore, once you are in the green zone, you can save up to 20% of your fuel. This saving, for a long trip, means a lot more sea.

The Honda BF100AK1 LRT models are NMEA2000® compliant. There is no need to modify the wiring because everything is set up. Simply plug the engine into the CANbus network - the boat's nervous system - for total connectivity and control. Then the outboard can be connected to other NMEA devices such as the navigation system, GPS, sonar devices, sounder and chartplotter. All information, including engine data, will be displayed via the multifunctional indicators.

HONDA BF100AK1 LRTU TECHNICAL SPECIFICATIONS

Net Power (kW): 73.6
Net Power (Hp): 100
Displacement: 1496 cm³
Shaft Length: Long
Dry Weight (Kg) : 166
Boosting: Electric
Initiation System: Electronic PGM-IG
Type of Control: Remote
Engine trim and lift: Electric
Transom height (mm): 537
Length (mm): 746
Width (mm): 449
Height (mm): 1566
Bore x stroke: 73 x 89.4 mm
Brand Engine: Honda
Engine Type: SOHC, 4-stroke
Number of Cylinders: 4
RPM at full throttle (rpm): 5300-6300
Cooling System: Water

Battery Charging Capacity (A): 35

Are you looking for an outboard with different specifications? Here you can find the entire Honda range or other brands specializing in the field.

Images are for guidance only.

Product features:

Fuel: Gasoline

Engine: SOHC, 4 tempi

Ignition: Electronic PGM-IG

Starting system: Electric

Engine capacity (cm³): 1496

Number cylinders: 4

Cylinders' position: In line

Cooling: Water (with thermostat)

Bore x stroke (mm): 73 x 89.4

Reduction ratio: 2.33

Rpm at full throttle (rpm): 5300 - 6300

Appearance and engine lifting: Electric

Transom height (mm): 537

Net power (kW): 73.6

Length (mm): 746

Width (mm): 449

Height (mm): 1566

Dry weight (Kg): 166

Shaft Length: L

Controls: Remote