



PRAMAC ES3000

Product price:

894,75 € tax excluded

Product description:

Product features:

Phase: Single phase

Maximum power single phase (KW): 2.6

Continuous power single phase (KW): 2.2

Maximum power single phase (KVA): 2.9

Continuous power single phase (KVA): 2.5

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 2 x 230V 16A IP54 SCHUKO

Engine: Honda GX160, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Ignition: Recoil

Starting system: Pull starter

Engine capacity (cm³): 163

Oil capacity (L): 0.6

Cooling: Air

Alternator: Brushless

Poles: 2

Fuel tank capacity (L): 11

Consumption (L/h): 0.9 at 75% of the load / 1.2 at 100% of the load

Running time (h): 12.5 at 75% of the load / at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 623



Width (mm): 409
Height (mm): 500
Dry weight (Kg): 43
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: Capacitor
Engine manufacturer: Honda