

PRAMAC ES5000 THREE PHASE

Product price:

1.815,00 € tax excluded

Product description:

Ø.

Product features:

Phase: Single phase / Three phase Maximum power single phase (KW): 3.04 Continuous power single phase (KW): 2.8 Maximum power single phase (KVA): 3.8 Continuous power single phase (KVA): 3.5 Maximum power three phase (KW): 5 Continuous power three phase (KW): 4.3 Maximum power three phase (KVA): 6.3 Continuous power three phase (KVA): 5.4 **Fuel: Gasoline** Frequency (Hz): 50 Voltage (V): 230 / 400 Sockets configuration: 1 x 400V 16A 3P+N+T CEE IP44 - 1 x 230V 16A SCHUKO IP54 - 1 x 230V 16A 2P+T CEE IP44 Engine: Honda GX270 Recoil, naturally aspirated Engine rpm (rpm): 3000 Speed governor: Mechanical Ignition: Recoil Starting system: Pull starter Engine capacity (cm³): 270 Oil capacity (L): 1.1 Cooling: Air Alternator: With brushes Poles: 2 Fuel tank capacity (L): 11

R

Consumption (L/h): 1.6 at 75% of the load / 2.2 at 100% of the load Running time (h): 6.6 at 75% of the load / 5 at 100% of the load Acoustic power: 97 dB(A) Acoustic pressure: 69 dB(A) at 7 m Length (mm): 729 Width (mm): 500 Height (mm): 536 Dry weight (Kg): 75 Silenced: No Super silenced: No Product type: Generator ATS Switch device : No Voltage regulator: Compound Engine manufacturer: Honda

R