



PRAMAC GBW22P OPEN WITH MANUAL CONTROL PANEL (MCP)

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 17.46

Continuous power three phase (KW): 15.42

Maximum power three phase (KVA): 21.82

Continuous power three phase (KVA): 19.78

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: PERKINS 404D-22G, naturally aspirated

Emissions Regulations: Stage 3A

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 2216

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10.6

Cooling: Water

Fuel tank capacity (L): 51

Consumption (L/h): 4 at 75% of the load / 5.3 at 100% of the load

Running time (h): 12.8 at 75% of the load / 9.7 at 100% of the load

Length (mm): 1600

Width (mm): 870

Height (mm): 950



Dry weight (Kg): 425

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Perkins