



DINGOL DG184G Three-phase 31.3KVA AVR

Product price:

1.564,00 € tax excluded

Product description:

DINGOL DG184G THREE-PHASE ALTERNATOR 31.3KVA AVR

DINGOL DG184G is a three-phase brushless alternator capable of delivering a maximum power of 31.3KVA complete with AVR voltage regulator.

DINGOL DG184G is equipped with a class H insulation system. All components are subjected to a specific coating and/or impregnation process to safeguard the functionality of the generator and to protect the critical parts in various conditions of use.

The resins and paints used are suitable to make resistant the surface of the static windings, and to give mechanical strength to all rotating components.

DINGOL DG184G is equipped with a fully connected auxiliary buffer winding contributes to drastically reduce oscillations in parallel, this helps to minimize waveform distortions.

DINGOL DG184G adopt the IP22 (NEMA1) standard for industrial use suitable to guarantee protection from normal weather conditions. For extreme weather conditions, the IP23 standard is also available, which provides protection against water up to 60° from vertical.

The absence of a brush mechanism and the high efficiency of the voltage regulator ensure a low level of interference with radio waves.

DINGOL DG184G is equipped with twelve terminal blocks and are delivered pre-configured in three-phase configuration unless otherwise specified by the customer. However, if it is necessary to change the configuration, a table of possible configurations is shown on the back of the termination box cover.

AVR VOLTAGE REGULATOR



The AVR voltage regulator allows to transfer in a constant way the necessary energy from the excitation stator to the main exciter independently from the power developed instant by instant by the generator.

The high efficiency of the AVR ensures operation even when the residual excitation current is very low. The output current from the excitation rotor that is used to supply the main exciter passes through a wave rectifier bridge.

TECHNICAL CHARACTERISTICS DINGOL DG184G

Type of phase: Three-phase
Voltage (V): 400
Frequency (Hz): 50
Revolutions per minute (rpm): 1500
Single-phase power (kVA): ----
Three-phase power (kVA): 40
Alternator type: constant speed
Voltage regulator: AVR
Brushless
Protection degree: IP22 (on request IP 23)
Weight (Kg): 240

Are you looking for an alternator with different characteristics? Here you can find the whole range DINGOL or other specialized brands.

Pictures and technical data are not binding.

Product features:

Phase: Three phase
Frequency (Hz): 50
Voltage (V): 400
Engine rpm (rpm): 1500
Three-phase power (KW): 25
Three-phase power (KVA): 31.3
Efficiency (%): 87
Protection degree: IP22
Length (mm): 630
Width (mm): 500
Height (mm): 670
Dry weight (Kg): 172
Brushes: No
PMG: Optional

Type of alternator: Constant Speed
Voltage regulator: AVR