



# PRAMAC GSL65D



## Product description:

Compliance with Directive 2000/14/EC on environmental noise emissions and the high level of safety, which minimizes the danger of unauthorized use or accidental damage, make this series of generators suitable for all industrial and residential applications.

DEUTZ diesel engines (prepared for BIODIESEL)

- ? Oil cooling with radiator
- ? MECCALTE electronic control alternators
- ? Galvanized casing with residential muffler
- ? Lifting hook and forklift base with trolleys
- ? Motor fluids and charged battery
- ? Oil extraction piping
- ? MCP cabinet with 4 service sockets (GSL65 optional)
- ? ETB terminal block power connection GSL65
- ? KPR Dispersed liquid collection basin (std ACP)

The images are purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 51.47

Continuous power three phase (KW): 48.76

Maximum power three phase (KVA): 64.34

Continuous power three phase (KVA): 60.95

Fuel: Diesel

Frequency (Hz): 50



Voltage (V): 400

Emissions Regulations: Stationary Use

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 5650

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 13.5

Cooling: Air

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 240

Consumption (L/h): 10.7 at 75% of the load / 14.7 at 100% of the load

Running time (h): 22.4 at 75% of the load / 16.3 at 100% of the load

Length (mm): 2200

Width (mm): 1000

Height (mm): 1620

Dry weight (Kg): 954

Inverter: No

AVR: Yes

Compound: No

Silenced: No

Super silenced: No