



# PRAMAC GSL65D AUTOMATIC

## Product description:

Using a single fluid for cooling and lubrication, LPG is one of the best choices for continuous use in harsh environmental conditions such as tropical areas.

Available in open or hooded versions, these generators are highly appreciated in the telecommunications, construction and defense sectors for their durability and reliability. All service points are accessible on one side to make maintenance quick and easy.

DEUTZ diesel engines  
MECCALTE electronic control alternators  
Ready for BIODIESEL  
? Oil cooling with radiator  
Industrial silencer  
Fork base with trolleys  
Motor fluids and charged battery

The images are purely indicative.

## Product features:

Phase: Three phase  
Maximum power three phase (KW): 48.76  
Continuous power three phase (KW): 46.23  
Maximum power three phase (KVA): 60.95  
Continuous power three phase (KVA): 57.79  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 400  
Emissions Regulations: Stationary Use



Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 91

Consumption (L/h): 9.9 at 75% of the load / 13.4 at 100% of the load

Running time (h): 9.2 at 75% of the load / 6.8 at 100% of the load

Length (mm): 2007

Width (mm): 758

Height (mm): 1841

Dry weight (Kg): 858

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Deutz