




NANNI QLS10T



Product description:

NANNI QLS10T MARINE GENERATOR 7.9KW

NANNI QLS10T is a three-phase marine generator equipped with a Kubota 4-stroke diesel engine capable of delivering a maximum power of 7.9KW.

NANNI QLS10T is equipped with a Kubota base engine used for years in marine and industrial applications all over the world.

Engine block in cast iron of tunnel type and gear distribution.

The NANNI QLS10T generator is equipped with an injector and a rapid heating glow plug and are positioned in the combustion chamber, ensuring the start of the engine even at low temperatures. The combustion chamber uses Kubota's exclusive E-TVCS system: the system allows optimal filling of the combustion chambers, significantly increasing efficiency.

NANNI QLS10T is complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible seawater pump with rubber impeller.

The instrument panel allows you to start and stop the generator, and gives you important information about the generator set when it is running. Check this information regularly when the generator set is running. If your instrument panel does not match the models described in this chapter, contact your authorized Nanni Diesel dealer.

The alternator of the NANNI QLS10T provides 7 KW of power in continuous operation and can produce up to 7.9 KW. Protection level IP23 (protection level available on request).

NANNI QLS10T TECHNICAL FEATURES

Maximum three-phase power: 7.9 KW

Continuous three-phase use power: 7 KW





Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Engine: Kubota, 4-stroke
Start: Electric
Consumption: 2.3 Lt/h at full load
Length: 959 mm
Width: 489 mm
Height: 624 mm
Weight: 251 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image is purely indicative.

Product features:

Phase: Three phase
Maximum power three phase (KW): 7.9
Continuous power three phase (KW): 7
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Engine: Kubota, 4 stroke
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 1123
Number cylinders: 3
Cylinders' position: In line
Oil capacity (L): 5.1
Cooling: Water
Inyección : Indirect (E-TVCS)
Alternator: Leroy Somer, electronic regulator
Bore x stroke (mm): 78 x 78.4
Consumption (L/h): 2.3 at 100% of the load
Length (mm): 959
Width (mm): 489
Height (mm): 624
Dry weight (Kg): 251

