



# NANNI QMF6M



## Product description:

### NANNI QMF6M SINGLE-PHASE GENERATOR 5KW

NANNI QMF6M is a generator equipped with a Kubota 4-stroke, diesel-powered engine capable of delivering a maximum single-phase power of 5KW.

The E-TVCS combustion system allows the NANNI QMF6M generator to meet the most stringent anti-pollution and noise standards, while also reducing fuel consumption.

The NANNI QMF6M is equipped with a dual-circuit coolant/seawater system to allow cooling of both the engine and the generator.

NANNI QMF6M is equipped with lacquered aluminum structure (alloy 5754 H111) with polyurethane paint of the soundproofing cabin allows to lower the noise to only 54 dB at 7 meters, which is the equivalent of a dishwasher. Access to interior parts is easy thanks to 4 removable panels.

Electrical connections, seawater inlet and outlet fittings, and the exhaust elbow are built into the cabin.

The instrument panel provides important information about the genset when it is operating. Check this information regularly when the generator set is operating.

The NANNI generator comes complete with a control panel with:  
on/key switch, oil pressure warning light, coolant temperature warning light, pre-heat light, battery charging light

## TECHNICAL FEATURES NANNI QMF6M

Maximum power Single-phase: 5 KW

Continuous use power Single-phase: 4.6 KW



Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Engine: Kubota, 4-stroke  
Number of cylinders: 2 in line  
Displacement: 479 cm<sup>3</sup>  
Bore & stroke: 67 x 68 mm  
Injection: indirect (E-TVCS)  
RPM: 3000  
Start: Electric  
Sound power: 54 dB at 7 meters  
Consumption: 2.2 Lt/h at full load  
Length: 650 mm  
Width: 480 mm  
Height: 530 mm  
Weight: 128 Kg

Are you looking for a generator with different characteristics? Here you can find the full range NANNI or other brands specializing in the field.

Images and technical data are not binding and may be subject to revision by the supplier.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 5  
Continuous power single phase (KW): 4.6  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Kubota, 4 stroke  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 479  
Number cylinders: 2  
Cylinders' position: In line  
Oil capacity (L): 1.9  
Cooling: Water  
Inyección : Indirect (E-TVCS)  
Alternator: Brushless  
Poles: 2  
Bore x stroke (mm): 67 x 68  
Consumption (L/h): 2.2 at 100% of the load

---

Length (mm): 650  
Width (mm): 480  
Height (mm): 530  
Dry weight (Kg): 128  
Super silenced: Yes