



# NANNI QMS10T



## Product description:

### NANNI QMS10T MARINE GENERATOR 7.7KW

NANNI QMS10T is a three-phase marine generator equipped with a Kubota, 4-stroke diesel engine capable of delivering a maximum power of 7.7KW.

The Nanni Diesel generator sets are the result of many years of experience in the development of marine engines and equipment designed for offshore use. The NANNI QMS10T is equipped with a Kubota base engine which has been used for years in marine and industrial applications throughout the world.

The cooling system allows the NANNI QMS10T to operate at an optimum temperature. In the case of closed-circuit heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The NANNI QMS10T is equipped with a closed-circuit heat exchanger.

The Kubota 4-stroke diesel engine is tested in all marine or industrial applications around the world, this engine ensures excellent performance and incredible reliability. The engine consists of cast iron tunnel type block and timing gear. The Super Glow system comes as standard equipment for cold weather starting.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS10T is improved, resulting in low fuel consumption.

NANNI QMS10T comes complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The NANNI QMS10T's alternator provides 8.8KW of power in continuous operation and can



---

produce up to 10KW. Protection level IP23 (protection level available on request).

#### TECHNICAL FEATURES NANNI QMS10T

Maximum power three-phase: 7.7 KW  
Three phase continuous use power: 6.8 KW  
Fuel: Diesel  
Voltage: 400 V  
Frequency: 50 Hz  
Engine: Kubota, 4 strokes  
Starting: Electric  
Consumption: 2.5 Lt/h at full load  
Length: 950 mm  
Width: 540 mm  
Height: 715 mm  
Weight: 271 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

#### **Product features:**

Phase: Three phase  
Maximum power three phase (KW): 7.7  
Continuous power three phase (KW): 6.8  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 400  
Engine: Kubota, 4 stroke  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1123  
Number cylinders: 3  
Cylinders' position: In line  
Oil capacity (L): 5.1  
Cooling: Water  
Inyección : Indirect (E-TVCS)  
Alternator: Electronic regulator  
Bore x stroke (mm): 78 x 78.4  
Consumption (L/h): 2.5 at 100% of the load

---

Length (mm): 950  
Width (mm): 540  
Height (mm): 715  
Dry weight (Kg): 271