

VTE MOVE 12000 F



Product description:

VTE MOVE12000F super-silenced 10 KW vehicle generator

VTE MOVE12000F single phase 10 KW vehicle generator with Lombardini 3000 rpm diesel engine with soundproofing capsule and supersilenced. The single-phase VTE MOVE12000F vehicle generator has an electric start.

The alternator of the VTE MOVE12000F single-phase vehicle generator has permanent magnets. Thanks to its casing, the MOVE12000F vehicle generator is very quiet and has noise emissions of only 54 dB(A). Designed with high quality components it has a reduced fuel consumption: only 0.35 Lt/KW/h.

Remote control and control of the MOVE12000F single-phase vehicle generator with:

- Hour meter
- Load indicator
- Automatic stop for low oil pressure and water overtemperature
- Starter motor release
- Quick connector and 15 meters of cable

Born from the deep-rooted experience of Volpi Tecno Energia in the field of vehicle generators, MOVE is the brand dedicated to generators for vehicular, military and residential use. From 4 KW and up, the vehicle generators in this range are the quietest, most compact and lightest with the same performance. The technologies developed by Volpi Tecno Energia are able to reduce the overall dimensions to a minimum, thus ensuring a lower weight and greater efficiency of the vehicle generators that are ideal for installation on trucks, military vehicles or any other type.

These vehicle generators are the quietest: in addition, vibrations are reduced to a minimum and make generators like MOVE12000F always competitive on the market. Thanks to the production flexibility of the Trieste plant and to the technical skills developed in the sector, Volpi Tecno Energia is able to design and manufacture customized products built ad hoc according to the customer's needs.

If you are looking for another product such as the MOVE12000F vehicular generator you can consult the entire catalogue of terrestrial generators.

Images and technical data are not binding.

Product features:

Phase: Single phase

Continuous power single phase (KW): 10

Continuous power single phase (KVA): 12

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Engine: Lombardini LDW1003

Engine rpm (rpm): 3000

Starting system: Electric

Number cylinders: 3

Cooling: A liquido totale a circuito chiuso con radiatore esterno

Alternator: Permanent magnets

Consumption (L/h): 0.35

Acoustic pressure: 54 dB(A)

Length (mm): 860

Width (mm): 580

Height (mm): 650

Dry weight (Kg): 220

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: No

Engine manufacturer: Lombardini