



PRAMAC LIFTER HAND PALLET TRUCK GS25S4 1150x525 DOUBLE ROLLER

Product price:

389,20 € tax excluded

Product description:

Maximize Efficiency with the PRAMAC LIFTER HAND PALLET TRUCK GS25S4

The PRAMAC LIFTER HAND PALLET TRUCK GS25S4 1150x525 DOUBLE ROLLER redefines efficiency and reliability in manual load management. This pedestrian-operated pallet truck, with its formidable 2500 Kg load capacity and unparalleled manual maneuverability, is the cornerstone of modern material control.

Elevating Material Handling Standards

Double Roller Design: Ensures smooth, stable movement for heavy loads, enhancing executional efficiency.

Ergonomic and Manual execution: Tailored for user control and comfort, facilitating ease in manual material handling tasks.

Pedestrian-Friendly execution: Features like an ergonomic handle make the PRAMAC LIFTER GS25S4 a standard in user-friendly manual pallet trucks.

Substantial Load Management: Capable of handling up to 2500 Kg, it's designed for the demands of bustling warehouses and manufacturing facilities.

Precision Lift and Transport: The 115 mm lift height and 1150x525 fork size are optimized for effective pallet handling, reducing physical strain.

Designed for Durability and Safety

The PRAMAC LIFTER GS Series, and particularly the PRAMAC LIFTER GS25S4 model, embodies practicality and safety. It is equipped with start and exit rollers for seamless operation and a more comfortable handle, reducing fatigue over long periods of use. The model's thoughtful design ensures it navigates narrow aisles and executes tight turns with ease, prioritizing operator safety and pallet security.

The inclusion of a maximum pressure valve prevents overloading, preserving the truck's structural integrity. Furthermore, its frame, treated with a high-temperature polyester powder



varnish, stands up against wear and environmental damage, embodying PRAMAC's commitment to durability.

The PRAMAC LIFTER Advantage

Choosing the PRAMAC LIFTER GS25S4 is more than an operational decision; it's an investment in efficiency and safety. This pallet truck not only meets but exceeds the requirements of intensive manual handling, offering a blend of performance, durability, and ergonomic design unmatched in the market.

Discover how the PRAMAC LIFTER GS25S4 can transform your material control processes, making your operations safer, more efficient, and more productive.

Learn about other similar products.

The images are only indicative of the product.

Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 2500

Load centre distance (mm): 600

Load axle to end forks (mm): 932

Wheel base (mm): 1192

Service weight (Kg): 63

Axle load, laden rear (Kg): 1796

Axle load, laden front (Kg): 767

Axle load, unladen front (Kg): 42

Axle load, unladen rear (Kg): 21

Tyres: front wheels: POLY.I. / NYLON

Tyres: rear wheels: NYLON

Diameter steering wheels (mm): 200

Width steering wheels (mm): 55

Diameter load rollers (mm): 82

Width load rollers (mm): 60

Quantity rear wheels: 4

Rear balancing axle: No

Tread front (mm): 155

Tread rear (mm): 375

Lift height (mm): 115

Height of tiller in drive position max (mm): 1160

Height lowered (mm): 85

Overall length (mm): 1550

Length to face of forks (mm): 400

Overall width (mm): 525

Thickness fork (mm): 55

Width fork (mm): 150

Lenght fork (mm): 1150

Distance between fork arms (mm): 525

Ground clearance at centre of wheelbase (mm): 30

Aisle width (mm): 1835

Turning radius (mm): 1367

Lifting speed laden (strokes): 13

Lifting speed unladen (strokes): 13

Weigher: No