



PRAMAC LIFTER SEMI-ELECTRIC STACKER TX10/16

Product price:

3.103,80 € tax excluded

Product description:

The TX Series are characterized by manual traction and electrohydraulic lifting technology. These stackers are very steady and are suitable for lifting very heavy loads safely. Version 12 (1.2 t) includes polyurethane wheels as standard to reduce resistance and effort required even with full load capacity.

Start key and battery cut-off (isolator) switch

The start key on the TX stacker performs a double function:

- switches the stacker on/off;
- is an emergency control, i.e. it completely stops battery power supply and thus prevents the lifting of forks.

Foot brake

The foot brake, which is available on the MX and TX machines, performs the parking brake function.

Tiller

The plastic cover increases the ergonomic character of the handle thus rendering the raising and transport operations even "lighter".

The 3-position control lever (down, neutral, up) is positioned on the steering wheel to foster manoeuvrability.

Adjustable buffers

The TX 12 version is equipped with adjustable buffers that minimize possible oscillation during lifting.



The images are purely indicative.

Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 1000

Load centre distance (mm): 600

Load axle to end forks (mm): 630

Wheel base (mm): 965

Service weight (Kg): 311

Axle load, laden rear (Kg): 1070

Axle load, laden front (Kg): 241

Axle load, unladen front (Kg): 210

Axle load, unladen rear (Kg): 101

Tyres: stabilizers wheels: RUBBER

Tyres: rear wheels: NYLON

Diameter load rollers (mm): 82

Width load rollers (mm): 70

Diameter stabilizers wheels front (mm): 200

Width stabilizers wheels front (mm): 50

Quantity rear wheels: 2

Tread front (mm): 620

Tread rear (mm): 410

Height mast lowered (mm): 1970

Normal free lifting (mm): 1510

Lift height (mm): 1510

Height mast extended (mm): 1970

Height of tiller in drive position max (mm): 1080

Height lowered (mm): 90

Overall length (mm): 1750

Length to face of forks (mm): 600

Overall width (mm): 750

Thickness fork (mm): 70

Width fork (mm): 150

Length fork (mm): 1150

Fork carriage width (mm): 650

Distance between fork arms (mm): 560

Ground clearance at centre of wheelbase (mm): 20

Aisle width (mm): 2336

Turning radius (mm): 1440

Lifting speed laden (m/s): 0.09

Lifting speed unladen (m/s): 0.12

Lowering speed laden (m/s): 0.4
Lowering speed unladen (m/s): 0.1
Lift motor power (KW): 1.6
Battery voltage (V): 12
Battery capacity min (Ah): 74
Battery capacity max (Ah): 74
Battery weight min (Kg): 18
Battery weight max (Kg): 18
Sound level at driver's ear: 67
Type of lifting: Electric