



PRAMAC LIFTER SEMI-ELECTRIC STACKER TX12/25

Product price:

4.033,40 € tax excluded

Product description:

The TX Series are characterized by manual traction and electrohydraulic lifting technology. These stackers are very steady and are suitable for lifting very heavy loads safely. Version 12 (1.2 t) includes polyurethane wheels as standard to reduce resistance and effort required even with full load capacity.

Start key and battery cut-off (isolator) switch

The start key on the TX stacker performs a double function:

- switches the stacker on/off;
- is an emergency control, i.e. it completely stops battery power supply and thus prevents the lifting of forks.

Foot brake

The foot brake, which is available on the MX and TX machines, performs the parking brake function.

Tiller

The plastic cover increases the ergonomic character of the handle thus rendering the raising and transport operations even "lighter".

The 3-position control lever (down, neutral, up) is positioned on the steering wheel to foster manoeuvrability.

Adjustable buffers

The TX 12 version is equipped with adjustable buffers that minimize possible oscillation during



lifting.

The images are purely indicative.

Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 1200

Load centre distance (mm): 600

Load axle to end forks (mm): 780

Wheel base (mm): 1155

Service weight (Kg): 415

Axle load, laden rear (Kg): 1122

Axle load, laden front (Kg): 493

Axle load, unladen front (Kg): 301

Axle load, unladen rear (Kg): 114

Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: NYLON

Diameter load rollers (mm): 82

Width load rollers (mm): 70

Diameter stabilizers wheels front (mm): 200

Width stabilizers wheels front (mm): 50

Quantity rear wheels: 2

Tread front (mm): 720

Tread rear (mm): 410

Height mast lowered (mm): 1780

Lift height (mm): 2410

Height mast extended (mm): 2985

Height of tiller in drive position max (mm): 1080

Height lowered (mm): 90

Overall length (mm): 1850

Length to face of forks (mm): 700

Overall width (mm): 850

Thickness fork (mm): 70

Width fork (mm): 150

Length fork (mm): 1150

Fork carriage width (mm): 650

Distance between fork arms (mm): 560

Ground clearance at centre of wheelbase (mm): 20

Aisle width (mm): 2540

Turning radius (mm): 1760

Lifting speed laden (m/s): 0.09
Lifting speed unladen (m/s): 0.12
Lowering speed laden (m/s): 0.4
Lowering speed unladen (m/s): 0.1
Lift motor power (KW): 2.2
Battery voltage (V): 24
Battery capacity min (Ah): 74
Battery capacity max (Ah): 74
Battery weight min (Kg): 36
Battery weight max (Kg): 36
Sound level at driver's ear: 67
Type of lifting: Electric