

# PRAMAC LIFTER MANUAL STACKER MX510



## Product description:

MX series is not only an excellent compromise between price and performance but is also a very resistant machine. Reinforced forks, a pulley made of steel and forks driven by 4 rollers to the position set are some of the main features of the high quality of this stacker. The machine is also equipped with a foot pedal for the lifting of forks, which considerably reduces the operator's effort.

## Foot brake

The foot brake, which is available on the MX and TX machines, performs the parking brake function.

## Tiller

- The plastic cover increases the ergonomic character of the handle thus rendering the raising and transport operations even "lighter".
- The 3-position control lever (down, neutral, up) is positioned on the steering wheel to foster manoeuvrability.

The images are purely indicative.

## Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 500

Load centre distance (mm): 600

Load axle to end forks (mm): 800

Wheel base (mm): 1240

Service weight (Kg): 185

Axle load, laden rear (Kg): 483

Axle load, laden front (Kg): 200  
Axle load, unladen front (Kg): 113  
Axle load, unladen rear (Kg): 72  
Tyres: stabilizers wheels: NYLON  
Tyres: rear wheels: NYLON  
Diameter load rollers (mm): 80  
Width load rollers (mm): 70  
Diameter stabilizers wheels front (mm): 150  
Width stabilizers wheels front (mm): 40  
Quantity rear wheels: 2  
Tread front (mm): 600  
Tread rear (mm): 380  
Height mast lowered (mm): 1490  
Normal free lifting (mm): 910  
Lift height (mm): 910  
Height mast extended (mm): 1490  
Height of tiller in drive position max (mm): 1090  
Height lowered (mm): 90  
Overall length (mm): 1650  
Length to face of forks (mm): 540  
Overall width (mm): 740  
Thickness fork (mm): 60  
Width fork (mm): 170  
Length fork (mm): 1150  
Fork carriage width (mm): 550  
Distance between fork arms (mm): 550  
Ground clearance at centre of wheelbase (mm): 30  
Aisle width (mm): 2166  
Turning radius (mm): 1400  
Lifting speed laden (m/s): 37  
Lifting speed unladen (m/s): 37  
Lowering speed laden (m/s): 0.16  
Lowering speed unladen (m/s): 0.05  
Type of lifting: Electric