



# PRAMAC LIFTER HAND PALLET TRUCK GS25S4 1350x525 DOUBLE ROLLER

Product price:

**763,70 € tax excluded**

## Product description:

GS series is a suitable practical solution meeting all the needs of manual handling. The GS PRO pallet truck is equipped as a standard with a start and exit roller and a more ergonomic handle.

## Maximum pressure valve

When the maximum load capacity is exceeded, oil pressure exceeds its maximum limit and the valve automatically locks the forks. Thus possible structural damage is avoided.

## Varnishing

Following an appropriate conditioning operation the frame is varnished with polyester powder at a temperature of 250° to guarantee maximum resistance to wear and atmospheric agents.

The images are purely indicative.

## Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 2500



Load centre distance (mm): 675  
Load axle to end forks (mm): 1132  
Wheel base (mm): 1392  
Service weight (Kg): 90  
Axle load, laden rear (Kg): 1711  
Axle load, laden front (Kg): 879  
Axle load, unladen front (Kg): 58  
Axle load, unladen rear (Kg): 32  
Tyres: front wheels: POLY.I. / NYLON  
Tyres: rear wheels: NYLON  
Diameter steering wheels (mm): 200  
Width steering wheels (mm): 55  
Diameter load rollers (mm): 82  
Width load rollers (mm): 60  
Quantity rear wheels: 4  
Rear balancing axle: No  
Tread front (mm): 155  
Tread rear (mm): 375  
Lift height (mm): 115  
Height of tiller in drive position max (mm): 1160  
Height lowered (mm): 85  
Overall length (mm): 1750  
Length to face of forks (mm): 400  
Overall width (mm): 525  
Thickness fork (mm): 50  
Width fork (mm): 150  
Length fork (mm): 1350  
Distance between fork arms (mm): 525  
Ground clearance at centre of wheelbase (mm): 35  
Aisle width (mm): 1985  
Turning radius (mm): 1567  
Lifting speed laden (strokes): 13  
Lifting speed unladen (strokes): 13  
Weigher: No