



# Pramac Lifter GS20S4 Pallet Jack 1150x525

Product price:

**400,00 € tax excluded**

## Product description:

Pramac Lifter GS20S4 Pallet Jack 1150x525: The Ultimate Manual Handling Solution

The Pramac Lifter GS20S4 Pallet Jack 1150x525 is the entry-level model in our manual pallet jack range, embodying the reliability and sturdiness that our products are known for. This Pramac Lifter GS20S4 Pallet Jack 1150x525 is the practical solution tailored to meet all manual handling needs, coming standard with a starter and exit roller and an ergonomically designed handle. The Pramac Lifter GS20S4 is perfect for scenarios where there is no need to move large quantities of material daily. Additionally, this model, available in our catalog, is proudly Made in Italy.

The wide variety of frames in the SPECIAL series allows for the handling of pallets of any size. Constructed with forks measuring 1150x525 cm and equipped with four rear wheels, this product has a load capacity of 2000 Kg and a lift height of 115 mm. The aisle width for stacking is 1822 mm, while the turning radius is 1367 mm.

Key Technical Features of the Pramac Lifter GS20S4 - 1150x525:

Type of propulsion: Manual  
Steering system: Walk-behind  
Load capacity: 2000 Kg  
Number of rear wheels: 4  
Lift height: 115 mm  
Total length: 1550 mm  
Total width: 525 mm  
Fork width: 160 mm  
Fork length: 1150 mm  
Width between forks: 525 mm  
Aisle width for stacking: 1822 mm  
Turning radius: 1367 mm





### Overload Protection Valve

An overload protection valve automatically locks the forks if the oil pressure exceeds its maximum limit when the load capacity is surpassed, preventing potential structural damage.

### Durable Paint

After undergoing a thorough preparation process, the frame is coated with polyester powder at a temperature of 250° to ensure maximum resistance to wear and weather conditions.

If you're in search of other types of products for the transportation and storage of goods, we invite you to browse our catalog for a wide selection of options.

Please note that images and technical data are provided for informational purposes and are not binding.

### Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 2000

Load centre distance (mm): 600

Load axle to end forks (mm): 945

Wheel base (mm): 1192

Service weight (Kg): 71

Axle load, laden rear (Kg): 1378

Axle load, laden front (Kg): 693

Axle load, unladen front (Kg): 48

Axle load, unladen rear (Kg): 23

Tyres: front wheels: POLY.I. / NYLON

Tyres: rear wheels: NYLON

Diameter steering wheels (mm): 200

Width steering wheels (mm): 55

Diameter load rollers (mm): 55

Width load rollers (mm): 58

Quantity rear wheels: 4

Rear balancing axle: No

Tread front (mm): 125

Tread rear (mm): 365

Lift height (mm): 115

Height of tiller in drive position max (mm): 1160

Height lowered (mm): 56.5

Overall length (mm): 1550

Length to face of forks (mm): 400

Overall width (mm): 525



---

Thickness fork (mm): 40  
Width fork (mm): 160  
Lenght fork (mm): 1150  
Distance between fork arms (mm): 525  
Ground clearance at centre of wheelbase (mm): 15  
Aisle width (mm): 1822  
Turning radius (mm): 1367  
Lifting speed laden (strokes): 13  
Lifting speed unladen (strokes): 13  
Weigher: No