

# PRAMAC LIFTER ELECTRIC PALLET TRUCK HX10E 1150x680

**Product price:**

**2.030,00 € tax excluded**

## **Product description:**

The HX10 series, which is available in both a manual and an electric version, allows for easy and light lifting to a height of 800 mm, thus becoming a practical work platform, which is suitable for places such as machine workshops. This pallet truck is also able to carry out the support function and material supply along the assembly and production lines.

## **Control lever**

The redesigned hydraulic unit allows for less effort at the steering wheel for all loads and a quick elevated function (30 cycles) for loads up to 150 Kg.

## **Emergency pushbutton**

The emergency pushbutton with a battery cut-off (isolator) switch function and an offload valve allows for a smoother lowering of the load; these are some of the devices that make the work safer and more efficient.

## **Front and rear stabilisers**

The new control linkage makes the entry onto the closed side of the pallet possible by slight lifting, which facilitates the successive handling phases. Furthermore, more machine stability has been obtained using load rollers in a more advanced position and by providing front stabilisers as a standard. Rear stabilizers, in turn, render work stable and safe even in the case of elevated loads once the 400 mm of lifting up have been exceeded.

## **Photo auto leveling system**

- An automatic system which, by means of a photocell, adjusts the height of the forks, thus



maintaining the work height set.

- An optical and acoustic signal is activated at every fork movement.
- Possibility of adjusting the photocell both in height and reading angle.
- Micro-switch, active both on the way up to prevent superfluous absorption of energy and on the way down to protect the operator.

The images are purely indicative.

### Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 1000

Load centre distance (mm): 600

Load axle to end forks (mm): 993

Wheel base (mm): 1231

Service weight (Kg): 146

Axle load, laden rear (Kg): 710

Axle load, laden front (Kg): 436

Axle load, unladen front (Kg): 118

Axle load, unladen rear (Kg): 28

Tyres: front wheels: RUBBER

Tyres: rear wheels: POLY.I.

Diameter steering wheels (mm): 200

Width steering wheels (mm): 50

Diameter load rollers (mm): 80

Width load rollers (mm): 50

Quantity rear wheels: 2

Tread front (mm): 155

Tread rear (mm): 587

Lift height (mm): 715

Height of tiller in drive position max (mm): 1300

Height lowered (mm): 85

Overall length (mm): 1690

Length to face of forks (mm): 540

Overall width (mm): 680

Thickness fork (mm): 48

Width fork (mm): 160

Length fork (mm): 1150

Distance between fork arms (mm): 680

Ground clearance at centre of wheelbase (mm): 21

---

Aisle width (mm): 2193  
Turning radius (mm): 1543  
Lifting speed laden (m/s): 0.08  
Lifting speed unladen (m/s): 0.13  
Lowering speed laden (m/s): 0.13  
Lowering speed unladen (m/s): 0.06  
Lift motor power (KW): 1.6  
Battery voltage (V): 12  
Battery capacity min (Ah): 60  
Battery capacity max (Ah): 60  
Battery weight min (Kg): 14  
Battery weight max (Kg): 14